

INDUSTRIAL COMPONENT DATA

SM25W SW 2046502 OBO BETTERMANN Threaded steel pipe with threaded sleeve, M25, 3000mm, Black, Painted, Steel..

Brand: OBO BETTERMANN | Manufacturer Part Number: SM25W SW



Manufacturer	OBO BETTERMANN
MPN / Reference	SM25W SW
Catalog number	2046502
Category	Metal installation tube
Minimum order	30 Pcs
Document ID	EO-74F877BE77
Generated	2026-07-31

Product Overview

Threaded steel pipe with threaded sleeve, M25, 3000mm, Black, Painted, Steel, St
SM25W SW Steel Threaded Tube with M25 Threaded Sleeve, 3000mm Deep Black Steel, St PES50 - Polyester/Epoxy
Black powder-coated steel tube, with thread. Pipe for electrical installations according to EN 61386-1, with threaded ends according to DIN EN 60423, for the mechanical protection of cables and conductors. With burr-free interior wall. Corrosion protection class 2 (medium). A connecting sleeve has already been threaded into each tube.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > metal pipe

Additional Product Information

Electrical installation pipe according to en 61386-1 with threaded ends to en 60423 for mechanical protection of cables.
With burr-free inner wall. One coupling is already screwed onto each pipe.

ETIM for 2046502 Rigid conduit systems (EC001173)

Feature Name

Feature Value

Material (EF002169)

Steel

Surface protection (EF000139)

Plastic-coated

Surface polished (EF006437)

No

Surface brushed (EF008705)
No
Model (EF000010)
Rigid
Connection 1 (EF000321)
Sleeve
Connection 2 (EF000322)
Outer thread metric
Colour (EF000007)
Black
Flush-mounted installation (EF007517)
Yes
Surface mounting (EF003681)
Yes
Suitable for concrete installation (EF003682)
Yes
Machine and systems installation (EF003683)
Yes
Suitable for underfloor installation (bitumen, hot asphalt) (EF003684)
Yes
Suitable for underfloor installation (screed) (EF003685)
Yes
Suitable for outdoor installation (EF003686)
No
Suitable for installation on wood (EF004162)
Yes
Suitable for hollow wall installation (EF003688)
Yes
Suitable for underground installation (EF003689)
No
Outer diameter (EF000015)
25 mm
Operating temperature (EF001742)
-45 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SM25W SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.