

INDUSTRIAL COMPONENT DATA

SVM16W SW 2046522 OBO BETTERMANN Threaded steel sleeve , M16x1,5, Black, Painted, Steel, St

Brand: OBO BETTERMANN | Manufacturer Part Number: SVM16W SW



Manufacturer	OBO BETTERMANN
MPN / Reference	SVM16W SW
Catalog number	2046522
Category	Coupler for installation tubes
Minimum order	25 Pcs
Document ID	EO-0362FDCA2B
Generated	2026-07-27

Product Overview

Threaded steel sleeve , M16x1,5, Black, Painted, Steel, St

Black powder-coated steel sleeve, with thread. Accessory part: coupling with thread according to EN 60423 to connect electrical installation pipes and 90° bends.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > metal pipe
--------------	---

Additional Product Information

Brushed surface no

CO2 Footprint (GWP) Cradle-to-Gate 0,1439 kg CO2e / 1 Piece

Colour Jet black; RAL 9005

Dimension M16x1,5

Dimension D 18,5 mm

Dimension d 16 mm

Dimension L 26 mm

Dimension m (mm) M16

Dimension t 2 mm

for pipe diameter 16 mm

Halogen-free no

Length 26 mm

Material Steel

Permitted temperature range, max. 250 °C

Permitted temperature range, min. -45 °C

Polished surface no

Size 16

Surface PES50 - Polyester/epoxy

Thread M16x1,5

Two-part no

Version for Thread

With inspection opening and lid no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SVM16W SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.