

INDUSTRIAL COMPONENT DATA

MS 21 D L 6M FT 1122945 OBO BETTERMANN Profile rails perforated, slot width 22 mm, 6000x42x41, Hot-dip galva..

Brand: OBO BETTERMANN | Manufacturer Part Number: MS4142P6000FT



Manufacturer	OBO BETTERMANN
MPN / Reference	MS4142P6000FT
Catalog number	1122945
Category	Mounting rail/-profile
Minimum order	6 m.
Document ID	EO-AE22670489
Generated	2026-07-28

Product Overview

Profile rails perforated, slot width 22 mm, 6000x42x41, Hot-dip galvanised, DIN EN ISO 1461, Steel, St MS4121 mounting rail, slot 22 mm, double, FT, perforated. Heavy-duty profile/mounting rail with continuous perforation in base, slot width 22 mm. Double version, i.e. two profile rails are interconnected on the base (clinched).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > MS Profile**

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 6,3643 kg CO2e / 1 Meter

Dimension 6000x41x42

Dimension L 6000 mm

Height 42 mm

Hole size 14x28 mm

Length 6000 mm

Maintain electrical functions no

Material Steel

Material thickness 2 mm

Profile shape C profile

Slot width 22 mm

Static value A 3,3 cm²

Static value Iy 5,38 cm⁴

Static value Iz 9,02 cm⁴
Static value Wy 1,28 cm³
Static value Wz 0,25 cm³
Surface Hot-dip galvanised
Type of perforation Perforated bar
Version for Double profile
Width 41 mm
With toothing yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MS4142P6000FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.