

**INDUSTRIAL COMPONENT DATA**

# MS 21 L 500 FT 1122936 OBO BETTERMANN Profile rails perforated, slot width 22 mm, 500x41x21, Hot-dip galvani..

Brand: OBO BETTERMANN | Manufacturer Part Number: MS4121P0500FT



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | OBO BETTERMANN         |
| MPN / Reference | MS4121P0500FT          |
| Catalog number  | 1122936                |
| Category        | Mounting rail/-profile |
| Minimum order   | 1 Pcs                  |
| Document ID     | EO-8D9BB0C669          |
| Generated       | 2026-08-01             |

## Product Overview

Profile rails perforated, slot width 22 mm, 500x41x21, Hot-dip galvanised, DIN EN ISO 1461, Steel, St MS4121 mounting rail, slot 22 mm, FT, perforated. Heavy-duty C profile rail for individual installation of support constructions, e.g. for cable trays or as a panel for switchgear cabinets. Can also be used for cable routing, in conjunction with clamp clips with a U foot.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                     |
|--------------|-------------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > MS Profile |
|--------------|-------------------------------------------------------------------------------------|

## Additional Product Information

Breakable no  
 CO2 Footprint (GWP) Cradle-to-Gate 1,5977 kg CO2e / 1 Piece  
 Dimension 500x41x21  
 Dimension L 500 mm  
 Drill hole spacing, centre 50 mm  
 Height 21 mm  
 Hole size 14x28 mm  
 Length 500 mm  
 Maintain electrical functions yes  
 Material Steel  
 Material thickness 2 mm  
 Profile shape C profile

Slot width 22 mm  
Static value A 1,65 cm<sup>2</sup>  
Static value I<sub>y</sub> 0,95 cm<sup>4</sup>  
Static value I<sub>z</sub> 4,51 cm<sup>4</sup>  
Static value W<sub>y</sub> 0,89 cm<sup>3</sup>  
Static value W<sub>z</sub> 2,2 cm<sup>3</sup>  
Surface Hot-dip galvanised  
Type of perforation Perforated back  
Version for Single profile  
Width 41 mm  
With perforation yes  
With tothing yes

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MS4121P0500FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.