

**INDUSTRIAL COMPONENT DATA**

# MS 41 L 3M 2 FT 1122964 OBO BETTERMANN Profile rails perforated, slot width 22 mm, 3000x41x41, Hot-dip galva..

Brand: OBO BETTERMANN | Manufacturer Part Number: MSL4141P3000FT



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | OBO BETTERMANN         |
| MPN / Reference | MSL4141P3000FT         |
| Catalog number  | 1122964                |
| Category        | Mounting rail/-profile |
| Minimum order   | 3 m.                   |
| Document ID     | EO-C943C02EEA          |
| Generated       | 2026-07-28             |

## Product Overview

Profile rails perforated, slot width 22 mm, 3000x41x41, Hot-dip galvanised, DIN EN ISO 1461, Steel, St MSL4141 mounting rail, slot 22 mm, FT, perforated. Heavy-duty C profile rail for individual installation of support constructions, e.g. for cable trays or as a panel for switchgear cabinets. Can also be used for cable routing, in conjunction with clamp clips with a U foot.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      OBO BETTERMANN &gt; VBS Connection and fastening systems - OBO BETTERMANN &gt; MS Profile

## Additional Product Information

Breakable no  
CO2 Footprint (GWP) Cradle-to-Gate 4,4328 kg CO2e / 1 Meter  
Dimension 3000x41x41  
Dimension L 3000 mm  
Drill hole spacing, centre 50 mm  
Height 41 mm  
Hole size 14x28 mm  
Length 3000 mm  
Maintain electrical functions yes  
Material Steel  
Material thickness 2 mm  
Profile shape C profile

Slot width 22 mm  
Static value A 2,45 cm<sup>2</sup>  
Static value I<sub>y</sub> 5,18 cm<sup>4</sup>  
Static value I<sub>z</sub> 7,56 cm<sup>4</sup>  
Static value W<sub>y</sub> 2,51 cm<sup>3</sup>  
Static value W<sub>z</sub> 2,69 cm<sup>3</sup>  
Surface Hot-dip galvanised  
Type of perforation Perforated back  
Version for Single profile  
Width 41 mm  
With perforation yes  
With toothing yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MSL4141P3000FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.