


INDUSTRIAL COMPONENT DATA

MS 41D L 3M 2 FT 1122671 OBO BETTERMANN Profile rails perforated, slot width 22 mm, 3000x82x41, Hot-dip galv..

Brand: OBO BETTERMANN | Manufacturer Part Number: MS4182P3000FT



Manufacturer	OBO BETTERMANN
MPN / Reference	MS4182P3000FT
Catalog number	1122671
Category	Mounting rail/-profile
Minimum order	3 m.
Document ID	EO-39B8332D80
Generated	2026-08-01

Product Overview

Profile rails perforated, slot width 22 mm, 3000x82x41, Hot-dip galvanised, DIN EN ISO 1461, Steel, St MS4182 mounting rail, slot 22 mm, double, FT, perforated. Heavy-duty profile/mounting rail with continuous perforation in base, slot width 22 mm. Double version, i.e. two profile rails are interconnected on the base (clinched).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > MS Profile**

Additional Product Information

Breakable no
 CO2 Footprint (GWP) Cradle-to-Gate 8,9341 kg CO2e / 1 Meter
 Dimension 3000x41x82
 Dimension L 3000 mm
 Height 82 mm
 Hole size 14x28 mm
 Length 3000 mm
 Maintain electrical functions no
 Material Steel
 Material thickness 2 mm
 Profile shape C profile
 Slot width 22 mm
 Static value A 4,9 cm²

Static value I_y 30,69 cm⁴
Static value I_z 15,11 cm⁴
Static value W_y 2,51 cm³
Static value W_z 2,69 cm³
Surface Hot-dip galvanised
Type of perforation Perforated bar
Version for Double profile
Width 41 mm
With toothing yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MS4182P3000FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.