

INDUSTRIAL COMPONENT DATA

MS4182P6000FT 1122673 OBO BETTERMANN Profile rails perforated, slot width 22 mm, 6000x82x41, Hot-dip galvani..

Brand: OBO BETTERMANN | Manufacturer Part Number: MS4182P6000FT



Manufacturer	OBO BETTERMANN
MPN / Reference	MS4182P6000FT
Catalog number	1122673
Category	Mounting rail/-profile
Minimum order	6 m.
Document ID	EO-A48CFADCB2
Generated	2026-07-31

Product Overview

Profile rails perforated, slot width 22 mm, 6000x82x41, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Profile MS4182P6000FT, perfor., groove width 22mm 6000x41x82 Steel, St, Hot dipped galvanized, DIN EN ISO 1461
MS4182 mounting profile, 22 mm slot, double, FT, perforated. Profile/mounting rail with through-hole in the bottom in reinforced version and with 22 mm groove width. In a double version, i.e. with two profiles joined together at the base (riveted).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > MS Profile

Additional Product Information

Static values:

A = 4,8569 cm²

I_y = 30,6909 cm⁴

I_z = 15,1124 cm⁴

W_y = 2,51257 cm³

W_z = 2,68608 cm³

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MS4182P6000FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.