

**INDUSTRIAL COMPONENT DATA**

# 822 22.5 FT 1014161 OBO BETTERMANN Attaching clip single lobe, 23mm, Hot-dip galvanised, DIN EN ISO 1461, St..

Brand: OBO BETTERMANN | Manufacturer Part Number: 822 22.5 FT



|                 |                   |
|-----------------|-------------------|
| Manufacturer    | OBO BETTERMANN    |
| MPN / Reference | 822 22.5 FT       |
| Catalog number  | 1014161           |
| Category        | Pipe saddle clamp |
| Minimum order   | 50 Pcs            |
| Document ID     | EO-BA491B6B05     |
| Generated       | 2026-07-29        |

## Product Overview

Attaching clip single lobe, 23mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St  
Fixing Clip 822 22.5 FT 1 ft 23mm Steel, St Hot Dip Galvanized, DIN EN ISO 1461  
Fastening clip 822, heavy duty, FT. Fastening clip, single-lobe, 23 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                               |
|--------------|-----------------------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Pizza metal fixation |
|--------------|-----------------------------------------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,0459 kg CO2e / 1 Piece  
Dimension 23mm  
Dimension A 11 mm  
Dimension b 20 mm  
Dimension D 22,5 mm  
Dimension H 21 mm  
Dimension L 23,5 mm  
Dimension L1 49 mm  
Dimension t 2 mm  
Distance to the wall no  
Fastening type Screw hole  
For diameter 22,5  
Halogen-free yes

Height 21 mm  
Hole size 6,5 x 10 mm  
Length 49 mm  
Material Steel  
Material thickness 2 mm  
Nominal diameter 22,5 mm  
Number of cables/pipes 1  
Plastic-covered no  
Size PG16  
Suitable in fire protection area no  
Surface Hot-dip galvanised  
UV-resistant yes  
Version for Single-lobe  
Width 20 mm

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 822 22.5 FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.