

INDUSTRIAL COMPONENT DATA

822 25 FT 1014501 OBO BETTERMANN Attaching clip single lobe, 25mm, Hot-dip galvanised, DIN EN ISO 1461, Steel..

Brand: OBO BETTERMANN | Manufacturer Part Number: 822 25 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	822 25 FT
Catalog number	1014501
Category	Pipe saddle clamp
Minimum order	50 Pcs
Document ID	EO-ED38E673A5
Generated	2026-07-28

Product Overview

Attaching clip single lobe, 25mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Fastening clip 822, heavy duty, FT. Fastening clip, single-lobe, 25 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Pizza metal fixation
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,0735 kg CO2e / 1 Piece

Dimension 25mm

Dimension A 11 mm

Dimension b 20 mm

Dimension D 25 mm

Dimension H 23,5 mm

Dimension L 25,5 mm

Dimension L1 53 mm

Dimension t 3 mm

Distance to the wall no

Fastening type Screw hole

For diameter 25

Halogen-free yes

Height 23,5 mm

Hole size 6,5 x 10 mm
Length 53 mm
Material Steel
Material thickness 2 mm
Nominal diameter 25 mm
Number of cables/pipes 1
Plastic-covered no
Size M25
Suitable in fire protection area no
Surface Hot-dip galvanised
UV-resistant yes
Version for Single-lobe
Width 20 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 822 25 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.