

INDUSTRIAL COMPONENT DATA

822 32 FT 1014528 OBO BETTERMANN Attaching clip single lobe, 32mm, Hot-dip galvanised, DIN EN ISO 1461, Steel..

Brand: OBO BETTERMANN | Manufacturer Part Number: 822 32 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	822 32 FT
Catalog number	1014528
Category	Pipe saddle clamp
Minimum order	100 Pcs
Document ID	EO-0104BE55E2
Generated	2026-08-01

Product Overview

Attaching clip single lobe, 32mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Fastening clip 822, heavy duty, FT. Fastening clip, single-lobe, 32 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Pizza metal fixation
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,1561 kg CO2e / 1 Piece

Dimension 32mm

Dimension A 13 mm

Dimension b 25 mm

Dimension D 32 mm

Dimension H 30 mm

Dimension L 32,5 mm

Dimension L1 68 mm

Dimension t 3 mm

Distance to the wall no

Fastening type Screw hole

For diameter 32

Halogen-free yes

Height 30 mm

Hole size 6,5 x 10 mm
Length 68 mm
Material Steel
Material thickness 2 mm
Nominal diameter 32 mm
Number of cables/pipes 1
Plastic-covered no
Size M32
Suitable in fire protection area no
Surface Hot-dip galvanised
UV-resistant yes
Version for Single-lobe
Width 25 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 822 32 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.