

INDUSTRIAL COMPONENT DATA

822 47 FT 1014366 OBO BETTERMANN Attaching clip single lobe, 47mm, Hot-dip galvanised, DIN EN ISO 1461, Steel..

Brand: OBO BETTERMANN | Manufacturer Part Number: 822 47 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	822 47 FT
Catalog number	1014366
Category	Pipe saddle clamp
Minimum order	100 Pcs
Document ID	EO-3E36DDB79F
Generated	2026-07-29

Product Overview

Attaching clip single lobe, 47mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Fastening clip 822, heavy duty, FT. Fastening clip, single-lobe, 47 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Pizza metal fixation
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,1614 kg CO2e / 1 Piece

Dimension 47mm

Dimension A 13 mm

Dimension b 25 mm

Dimension D 47 mm

Dimension H 45 mm

Dimension L 30 mm

Dimension L1 81 mm

Dimension t 3 mm

Distance to the wall no

Fastening type Screw hole

For diameter 47

Halogen-free yes

Height 45 mm

Hole size 6,5 x 10 mm
Length 81 mm
Material Steel
Material thickness 3 mm
Nominal diameter 47 mm
Number of cables/pipes 1
Plastic-covered no
Size PG36
Suitable in fire protection area no
Surface Hot-dip galvanised
UV-resistant yes
Version for Single-lobe
Width 25 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 822 47 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.