

INDUSTRIAL COMPONENT DATA

823 59.3 FT 1015486 OBO BETTERMANN Attaching clip two lobe, 59,3mm, Hot-dip galvanised, DIN EN ISO 1461, Ste..

Brand: OBO BETTERMANN | Manufacturer Part Number: 823 59.3 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	823 59.3 FT
Catalog number	1015486
Category	Pipe saddle clamp
Minimum order	100 Pcs
Document ID	EO-B63EDD66FC
Generated	2026-08-02

Product Overview

Attaching clip two lobe, 59,3mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Fastening clip 823, heavy duty. Fastening clip, double-lobe, 59.3 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Pizza metal fixation**

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,2486 kg CO2e / 1 Piece

Dimension 59,3mm

Dimension A 116 mm

Dimension B 92 mm

Dimension b 25 mm

Dimension d 6,5 mm

Dimension D 59,3 mm

Dimension e 10 mm

Dimension H 55 mm

Dimension t 3 mm

Distance to the wall no

Fastening type Screw hole

For diameter 59,3

Halogen-free yes

Height 55 mm
Hole size 6,5 x 10 mm
Length 116 mm
Material Steel
Material thickness 3 mm
Nominal diameter 59,3 mm
Number of cables/pipes 1
Plastic-covered no
Suitable in fire protection area no
Surface Hot-dip galvanised
UV-resistant yes
Version for Two-lobe
Width 25 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 823 59.3 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.