

INDUSTRIAL COMPONENT DATA

4759 4.0X40 3192245 OBO BETTERMANN Sprint screw countersunk head, cross drive, 4x40mm, Electrogalvanised, ye..

Brand: OBO BETTERMANN | Manufacturer Part Number: 4759 4.0x40



Manufacturer	OBO BETTERMANN
MPN / Reference	4759 4.0x40
Catalog number	3192245
Category	Chipboard screw
Minimum order	200 Pcs
Document ID	EO-0761D69FF7
Generated	2026-08-02

Product Overview

Sprint screw countersunk head, cross drive, 4x40mm, Electrogalvanised, yellow passivated, Steel, St Sprint screw, with Phillips slot. Hardened steel, electrogalvanised and Hostaflon-coated. Countersunk head with Phillips head (Pozidriv size 2 except Ø 6 mm Pozidriv size 3). The use of Sprint screws leads to considerably reduced screw-in times compared with standard screws. This noticeable benefit is achieved by the point with the first thread, which leads onto the double thread beyond. Areas of use: wood, chipboard, Rigips panels, plastic anchors.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Washers

Additional Product Information

Dimension 4x40mm
Dimension D 4 mm
Dimension L 40 mm
Hardened yes
Head diameter 7,5 mm
Head shape Countersunk head
Length 40 mm
Material Steel
Screw system Pozidrive PZ

Surface Electrogalvanized

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 4759 4.0x40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.