

INDUSTRIAL COMPONENT DATA

4759 6.0x60 3192644 OBO BETTERMANN Sprint screw countersunk head, cross drive, 6x60mm, Electrogalvanised, ye..

Brand: OBO BETTERMANN | Manufacturer Part Number: 4759 6.0x60



Manufacturer	OBO BETTERMANN
MPN / Reference	4759 6.0x60
Catalog number	3192644
Category	Chipboard screw
Minimum order	200 Pcs
Document ID	EO-DF41FFDC93
Generated	2026-08-02

Product Overview

Sprint screw countersunk head, cross drive, 6x60mm, Electrogalvanised, yellow passivated, Steel, St
Sprint 4759 6.0x60 lag screw, countersink cab., cross action 6x60mm Steel, St, electrozinc, EN ISO 19598 / EN ISO 4042
Sprint screw, with cross slot. Hardened, electro-galvanized steel coated with Hostaflon (PTFE). Countersunk head with cross groove (screwdriver size 2, except for the Ø of 6 mm which is size 3). The use of SPRINT screws leads to a considerable reduction in screwdriving times compared to conventional systems. This remarkable advantage can be perceived thanks to the thread of the 1-step gripping tip, which makes it easy to enter the 2-step thread. Fields of application: wood, chipboard, cardboard panchas, plaster, plastic dowels.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Washers
--------------	--

Additional Product Information

Hardened steel, electrogalvanised and yellow passivated, as well as Hostaflon-coated, countersunk head with Philips head (Pozidrive size 2 except Ø 6 mm Pozidrive size 3).

The use of Sprint screws leads to considerably reduced screw-in times compared with standard screws. This noticeable benefit is achieved by the point with the first thread, which leads onto the double thread beyond.

Areas of use: wood, chipboard, Rigips panels, plastic anchors.

ETIM for 3192644 Fixings and fasteners (EC002385)

Feature Name

Feature Value

Material (EF002169)

Steel

Surface protection (EF000139)

Galvanic/electrolytic zinc plated

Surface treatment (EF025109)

Coated

Hardened (EF004739)

Yes

Countersunk head (EF013941)

Yes

Screwing system (EF000013)

Pozidriv PZ

Head diameter (EF001001)

11 mm

Length (EF001438)

60 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 4759 6.0x60 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.