

INDUSTRIAL COMPONENT DATA

A22NL-BNM-TGA-P100-GC A2226546C

A22NLBNMTGAP100GC OMRON Push-button A22NL Ø22, plastic, enrrasado, momentane..

Brand: OMRON | Manufacturer Part Number: A22NL-BNM-TGA-P100-GC



Manufacturer	OMRON
MPN / Reference	A22NL-BNM-TGA-P100-GC
Catalog number	A22NLBNMTGAP100GC
Category	Push button, complete
Minimum order	5 Pcs
Document ID	EO-E85106DC0A
Generated	2026-08-06

Product Overview

Push-button A22NL Ø22, plastic, enrrasado, momentaneo, green,green led, 1NO, 24 VDC, push-in

Pushbutton A22NL 22, plastic, shed, momentary, green, green LED, 1NO, 24 VDC, push-in

Pushbutton A22NL Ø22, bezel plastic, FLAT, MOMENTARY, CAP COLOR Transparent GREEN, LED GREEN, 1NO, 24 VDC, push-in terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Industrial Limit switches / Pushbuttons > A22
--------------	---

Additional Product Information

Variety of bezel and color options with aesthetic design.

Mounting depth less than 46.8 mm below panel.

Up to 6 contact blocks (3 contact blocks across and 2 rows deep).

Symmetrical contact block.

Push-in Plus terminal block type.

Snap-in switch unit for quick and easy mounting.

RoHS compliant.

ETIM for 673634 Low-voltage industrial controls and switchgear (EC001028)

Feature Name

Feature Value

Colour front ring (EF002429)

Black

Type of button (EF001546)

Flat

Colour button (EF000190)

Green

Degree of protection (NEMA) (EF011959)

4X

Degree of protection (IP) (EF005474)

IP66

Construction type lens (EF006253)

Round

Material front ring (EF005972)

Plastic

Type of electric connection (EF003961)

Spring clamp connection

With front ring (EF006014)

Yes

Spring-return (EF001407)

Yes

Switching function latching (EF007447)

No

Suitable for lighting (EF001142)

No

Number of contacts as change-over contact (EF008257)

0

Number of contacts as normally open contact (EF008256)

1

Supply voltage lamp (EF006522)

24 V

Height opening (EF004778)

22.3 mm

Number of contacts as normally closed contact (EF008255)

0

Width opening (EF004565)

22.3 mm

Hole diameter (EF000079)

22 mm

Number of command positions (EF001372)

1

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / A22NL-BNM-TGA-P100-GC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.