

INDUSTRIAL COMPONENT DATA

D4C-4332 D4CN4332E D4C4332 OMRON Sealed Flat Plunger roller sealed LED 0.1 TO

Brand: OMRON | Manufacturer Part Number: D4C-4332



Manufacturer	OMRON
MPN / Reference	D4C-4332
Catalog number	D4C4332
Category	End switch
Minimum order	1 Pcs
Document ID	EO-82EA43C099
Generated	2026-08-03

Product Overview

Sealed Flat Plunger roller sealed LED 0.1 TO

Compact enclosed limit switch, sealed roller plunger, 0.1 A 125 VAC, 0.1 A 30 VDC, 5 m VCTF oil-resistant cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Industrial Limit switches / Pushbuttons > D4C

Additional Product Information

16 mm flat compact size
Rugged metal housing
Models with M12 connector or oil resistant VCTF cable
Specifications & ordering info
Ordering Information
Actuator type
Load range (VDC)1
Operation LED indicator
Connection method
Order code
0.8 W to 60 W max
No
Yes
Plunger

n
?
-
?
2
D4CC-3001
3 m
D4C-1201
-
?
?
D4CC-4001
3 m
D4C-3201
Sealed plunger
?
-
?
D4CC-3031
3 m
D4C-1231
-
?
?
D4CC-4031
3 m
D4C-3231
Plunger with M14 mounting
?
-
?
D4CC-3041
3 m
D4C-1241
-
?
?
D4CC-4041
3 m
D4C-3241
Roller plunger
?
-
?
D4CC-3002
3 m
D4C-1202

-
?
?
D4CC-4002
3 m
D4C-3202
Sealed roller plunger
?
-
?
D4CC-3032
3 m
D4C-1232
-
?
?
D4CC-4032
3 m
D4C-3232
Roller plunger with M14 mounting
?
-
?
D4CC-3042
3 m
D4C-1242
-
?
?
D4CC-4042
3 m
D4C-3242
Crossroller plunger
?
-
?
D4CC-3003
3 m
D4C-1203
-
?
?
D4CC-4003
3 m
D4C-3203
Sealed crossroller plunger
?

-
?
D4CC-3033
3 m
D4C-1233
-
?
?
D4CC-4033
3 m
D4C-3233
Crossroller plunger with M14 mounting
?
-
?
D4CC-3043
3 m
D4C-1243
-
?
?
D4CC-4043
3 m
D4C-3243
Roller lever
?
-
?
D4CC-3024
3 m
D4C-1220
-
?
?
D4CC-4024
3 m
D4C-3220
Coil spring
?
-
?
D4CC-3050
3 m
D4C-1250
-
?
?

D4CC-4050

3 m

D4C-3250

Specifications

Voltage and current rating

Model

Rated voltage

Rated current³

Non-inductive load

Inductive load

Inrush current

Applicable load range

(5 to 30 VDC)

Resistive load

Lamp load

Inductive load

Motor load

NC

NO

NC

NO

NC

NO

NC

NO

NC

NO

D4C-1???

125 VAC

5 A

5 A

1.5 A

0.7 A

3 A

3 A

2.5 A

1.3 A

20 A max.

10 A max.

-

250 VAC

2 A

5 A

5 A

1 A

0.5 A

2 A

2 A
1.5 A
0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / D4C-4332 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.