

INDUSTRIAL COMPONENT DATA

E3ZM-CT81 2M E3ZM0097E E3ZMCT812M OMRON Metal cc 3h Barrier 15m PNP IP67g Cable 2m

Brand: OMRON | Manufacturer Part Number: E3ZM-CT81 2M



Manufacturer	OMRON
MPN / Reference	E3ZM-CT81 2M
Catalog number	E3ZMCT812M
Category	Through beam photoelectric sensor
Minimum order	1 Pcs
Document ID	EO-0B8BB01158
Generated	2026-07-29

Product Overview

Metal cc 3h Barrier 15m PNP IP67g Cable 2m

Photoelectric sensor, rectangular housing, stainless steel, oil-resistant, infrared LED, through-beam, 15 m, PNP, Light-ON/Dark-ON, 2 m cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Photoelectric sensors > E3Z

Additional Product Information

ShapeCuboidSensing methodThrough-beamSensing distance15000 mmSetting methodManual adjustmentConnection methodCableCable length2 mOutput typePNPOperation modeDark-ON, Light-ONResponse time1 msMaterial housingStainless steelThread sizeOtherProduct Width (unpacked)10.8 mmProduct Height (unpacked)32 mmProduct Depth (unpacked)21 mmType of lightInfrared lightPower supply voltage10-30 VFeaturesOil-resistantDegree of protection (IP)IP67/IP69K

ETIM for 232309 Sensors (EC002716)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cuboid

Scope of delivery of the one-way system (EF004032)

Transmitter and receiver

Laser protection class (EF004027)

None

Degree of protection (NEMA) (EF011959)

Other

Degree of protection (IP) (EF005474)

IP67

Setting procedure (EF003994)

Manual adjustment

Material of optical surface (EF004134)

Plastic

Sensing mode (EF007503)

Light-/dark switching

Type of interface for safety communication (EF003956)

Other

Type of switch function (EF003963)

Programmable/configurable

Type of electric connection (EF003961)

Cable

Housing material (EF001596)

Metal

Type of light (EF004029)

Infrared light

Material of cable sheath (EF004136)

Polyvinyl chloride (PVC)

Type of switching output (EF003962)

PNP

Operation agent-safety class (EF003982)

Safety class 3

Explosion safety category for gas (EF003997)

None

With communication interface RS-485 (EF007314)

No

Analogue output -10 V ... +10 V (EF006...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E3ZM-CT81 2M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.