

INDUSTRIAL COMPONENT DATA

CP1E-N60DR-A 333293 CP1EN60DRA OMRON CPU 36/24 I/O AC Relay Outputs 8K Program 8K Data

Brand: OMRON | Manufacturer Part Number: CP1E-N60DR-A



Manufacturer	OMRON
MPN / Reference	CP1E-N60DR-A
Catalog number	CP1EN60DRA
Category	PLC CPU-module
Minimum order	1 Pcs
Document ID	EO-127FA84F53
Generated	2026-08-01

Product Overview

CPU 36/24 I/O AC Relay Outputs 8K Program 8K Data

PLC, 100-240 VAC supply, 36 x 24 VDC inputs, 24 x relay outputs 2 A, 8K steps program + 8K words data memory, RS-232C port

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Control Systems > CPM2C

Additional Product Information

Specifications

Supply voltage type AC

Number of digital inputs 36

Input type PNP/NPN

Number of digital outputs 24

Output type Relay

Program capacity 8 K steps

Data memory capacity 8 K words

Logic execution time 1.19 µs

Communication port(s) Serial RS-232C, USB

Number of Ethernet ports 0

Number of USB ports 1

Number of RS-232 ports 1

Number of RS-485 ports 0

Communication option(s) CompoBus/S Slave, Ethernet TCP/IP, Serial RS-232C, Serial RS-422, Serial RS-485

Max. encoder input frequency 100 kHz

Max. number of PTP axes 0

Max. pulse output frequency 0 kHz

Function Block programming

Battery-free memory backup

Real-time clock

Analog option boards

Max. number of analog I/O channels 28

Max. number of local I/O points 180

Max. number of expansion units 3

Built-in auxiliary 24 VDC output 300 mA

Operating temperature range 0-55 °C

Height 90 mm

Width 195 mm

Depth 85 mm

Weight 850 g

Accessories

CP1W-BAT01 Battery for the CP1 PLC

CP1W-CIF01 CP1 RS-232C (15 m max.) serial communication option board

CP1W-CIF11 CP1 RS422/485 (50 m max.) serial communication option board

CP1W-CIF12-V1 CP1 RS422/485 (isolated 500 m max.) serial communication option board

CP1W-CIF41 CP1 Ethernet communications option, 1 x RJ45 socket

CP1W-CN221 USB Programming cable, A-type male to B-type male, 1.8 m

CP1W-CN811 I/O expansion cable for CP1-series, 80 cm

CXONE-LT01-EV4 CX-One Lite v4.x software, for Windows 2000/XP/Vista, single-user licence only, (requires CDs, CXOne-LTCD-EV4), limited to program the CPx PLC....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / CP1E-N60DR-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.