

## INDUSTRIAL COMPONENT DATA

# CP1L-M30DR-A CP1W9241M CP1LM30DRA,1 OMRON CPU 18/12 I/O AC relay Outputs

Brand: OMRON | Manufacturer Part Number: CP1L-M30DR-A



|                 |                |
|-----------------|----------------|
| Manufacturer    | OMRON          |
| MPN / Reference | CP1L-M30DR-A   |
| Catalog number  | CP1LM30DRA.1   |
| Category        | PLC CPU-module |
| Minimum order   | 1 Pcs          |
| Document ID     | EO-C1496B05F7  |
| Generated       | 2026-08-03     |

## Product Overview

CPU 18/12 I/O AC relay Outputs

PLC, 100-240 VAC supply, 18 x 24 VDC inputs, 12 x relay outputs 2 A, 10K steps program + 32K words data memory

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path OMRON &gt; Control Systems

## Additional Product Information

Supply voltage typeACNumber of digital inputs18Input typePNP/NPNNumber of digital outputs12Output typeRelayProgram capacity10 K stepsData memory capacity32 K wordsLogic execution time0.55 µsCommunication port(s)USBNumber of Ethernet ports0Number of USB ports1Number of RS-232 ports0Number of RS-485 ports0Communication option(s)Serial RS-232C, Serial RS-422, Serial RS-485Number of encoder input channels4Max. encoder input frequency100 kHzMax. number of PTP axes0Max. pulse output frequency0 kHzFunction Block programmingBattery-free memory backupReal-time clockAnalogue option boardsMax. number of analogue I/O channels25Max. number of local I/O points150Max. number of expansion units3Built-in auxiliary 24 VDC output300 mAOperating temperature range0-55 °CProduct Height (unpacked)90 mmProduct Width (unpacked)130 mmProduct Depth (unpacked)85 mmProduct Weight (unpacked)610 g ETIM for 668695 PLC's (EC000236)

Feature Name

Feature Value

Performance level according to EN ISO 13849-1 (EF007399)

Level a

Model (EF000010)

Compact

SIL according to IEC 61508 (EF009889)

None

Voltage type (supply voltage) (EF002991)

AC

Explosion safety category for gas (EF003997)

None

Explosion safety category for dust (EF003998)

None

Type of memory (EF002996)

FLASH

Radio standard UMTS (EF008525)

No

Supporting protocol for EtherCAT (EF017564)

No

Appendant operation agent (Ex ib) (EF004142)

No

Supporting protocol for other bus systems (EF003062)

Yes

Supporting protocol for SERCOS (EF006657)

No

IO link master (EF...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / CP1L-M30DR-A with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.