

INDUSTRIAL COMPONENT DATA

D4B-2A15N D4BN2502A D4B2A15N OMRON Limit switch, stainless steel roller lever, DPDB 2-NC, slow action, 10 A,..

Brand: OMRON | Manufacturer Part Number: D4B-2A15N



Manufacturer	OMRON
MPN / Reference	D4B-2A15N
Catalog number	D4B2A15N
Category	End switch
Minimum order	1 Pcs
Document ID	EO-800983E152
Generated	2026-08-05

Product Overview

Limit switch, stainless steel roller lever, DPDB 2-NC, slow action, 10 A, G1/2 conduit

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Safety > D4B

Additional Product Information

Material housingAluminiumActuator typeRoller leverActuator detailMetal rollerConnection methodTerminal blockConduit sizeG1/2Cable entry directionBottomNumber of contacts, normally-open0Number of contacts, normally-closed2Make before breakSwitch actionSlow actionDirect opening mechanism
ETIM for 172192 Sensors (EC000030)
Feature Name
Feature Value
Explosion safety category for dust (EF003998)
None
Construction type housing (EF004008)
Cuboid
Degree of protection (NEMA) (EF011959)
6P
Coating housing (EF001601)
Other
Degree of protection (IP) (EF005474)

IP67

Alignment of the control element (EF008793)

Roller cam straight

Type of control element (EF006976)

Roller lever

Type of interface for safety communication (EF003956)

None

Type of electric connection (EF003961)

Other

Type of interface (EF006977)

None

Switching function (EF000189)

Slow-action switch

Housing material (EF001596)

Metal

Explosion safety category for gas (EF003997)

None

Switching function latching (EF007447)

No

With status indication (EF001602)

No

Suitable for safety functions (EF001597)

Yes

Forced opening (EF006694)

Yes

Output electronic (EF006987)

No

Number of contacts as change-over contact (EF008257)

0

Number of contacts as normally open contact (EF008256)

0

Rated operation current I_e at AC-15, 230 V (EF001385)

10 A

Rated operation current I_e at DC-13, 125 V (EF007085)

0.8 A

Number of safety auxiliary contacts (EF006940)

0

Rated operation current I_e at DC-13, 24 V (EF007087)

6 A

Rated operation current I_e at DC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / D4B-2A15N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.