

INDUSTRIAL COMPONENT DATA

D4F-120-5D D4F 0041A D4F1205D OMRON Metal IP67 1NC/1NO Plunger Lever Roller plunger 5m vert.

Brand: OMRON | Manufacturer Part Number: D4F-120-5D



Manufacturer	OMRON
MPN / Reference	D4F-120-5D
Catalog number	D4F1205D
Category	End switch
Minimum order	1 Pcs
Document ID	EO-54AEA7CC7E
Generated	2026-08-03

Product Overview

Metal IP67 1NC/1NO Plunger Lever Roller plunger 5m vert.

Metallic IP67 1NC/1NA Roller Lever Plunger 5m vert.

Small Safety Limit Switch, 1NC/1NO slow-action, roller lever, 5 m cable, vertical cable exit

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Safety > Others
--------------	-------------------------

Additional Product Information

Slim-size housing

Direct opening mechanism

Roller or plunger actuators

Pre-wired versions

ETIM for 134019 Sensors (EC000030)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Construction type housing (EF004008)

Cuboid

Degree of protection (NEMA) (EF011959)

Other

Coating housing (EF001601)
Other
Degree of protection (IP) (EF005474)
IP67
Alignment of the control element (EF008793)
Roller cam straight
Type of control element (EF006976)
Roller lever
Type of interface for safety communication (EF003956)
None
Type of electric connection (EF003961)
With cable preassembled
Type of interface (EF006977)
None
Switching function (EF000189)
Slow-action switch
Housing material (EF001596)
Metal
Explosion safety category for gas (EF003997)
None
Switching function latching (EF007447)
No
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
Yes
Forced opening (EF006694)
Yes
Output electronic (EF006987)
No
Number of contacts as change-over contact (EF008257)
0
Number of contacts as normally open contact (EF008256)
1
Rated operation current I_e at AC-15, 230 V (EF001385)
0.75 A
Rated operation current I_e at DC-13, 125 V (EF007085)
0.55 A
Number of safety auxiliary contacts (EF006940)
0
Rated operation current I_e at DC-13, 230 V (EF001386)
0.27 A
Number of contacts as normally closed contact (EF008255)
1
Rated operation current I_e at AC-15, 125 V (EF007082)
1.5 A
Width sensor (EF007094)

30 mm

Height of sensor (EF007283)

94.65 mm

Length of senso...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / D4F-120-5D with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.