

INDUSTRIAL COMPONENT DATA

E2A-S08KN04-M3-B1 E2A 7465E E2AS08KN04M3B1OMS OMRON Stainless steel Short-3h NoEnr 4mm M8 PNP NA M8 Connecto..

Brand: OMRON | Manufacturer Part Number: E2A-S08KN04-M3-B1



Manufacturer	OMRON
MPN / Reference	E2A-S08KN04-M3-B1
Catalog number	E2AS08KN04M3B1OMS
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-E21BC9CEB8
Generated	2026-08-06

Product Overview

Stainless steel Short-3h NoEnr 4mm M8 PNP NA M8 Connector 4pines

Proximity sensor, inductive, stainless steel, short body, M8, unshielded, 4mm, DC, 3-wire, PNP-NO, M8 plug-in

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Proximity Sensors > E2A

Additional Product Information

SizeM8Mounting typeNon-flushSensing distance4 mmOutput typePNPOperation modeNOConnection methodConnector
M8 - 4 pinMaterial housingStainless steelCable specifications-Overall length of sensor39 mmThread length21 mmDegree of
protection (IP)IP67/IP69K

ETIM for 659185 Sensors (EC002714)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cylinder, screw-thread

Degree of protection (NEMA) (EF011959)
Other
Coating housing (EF001601)
Other
Mechanical mounting condition for sensor (EF004041)
Not flat
Performance level according to EN ISO 13849-1 (EF007399)
None
Type of interface for safety communication (EF003956)
None
Type of actuation (EF006949)
Metallic Target
Type of switch function (EF003963)
Normally open contact
Type of electric connection (EF003961)
Connector M8
Type of interface (EF006977)
None
SIL according to IEC 61508 (EF009889)
None
Housing material (EF001596)
Metal
Type of switching output (EF003962)
PNP
Explosion safety category for gas (EF003997)
None
Cascadable (EF000507)
Yes
With monitoring function downstream switching devices (EF004052)
No
Compression-resistant (EF007106)
No
Suitable for safety functions (EF001597)
No
Number of protected contact energized outputs (EF003952)
0
Number of semiconductor outputs with signalling function (EF003945)
1
Number of protected semiconductor outputs (EF003951)
0
Diameter sensor (EF007111)
8 mm
Switching distance (EF003647)
4 mm
Length of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2A-S08KN04-M3-B1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.