

INDUSTRIAL COMPONENT DATA

E2A-S08LS02-M3-B3 E2A 7601A E2AS08LS02M3B3OMS OMRON Stainless steel Long-3h Enr 2mm M8 PNP NO+NC Connector M..

Brand: OMRON | Manufacturer Part Number: E2A-S08LS02-M3-B3



Manufacturer	OMRON
MPN / Reference	E2A-S08LS02-M3-B3
Catalog number	E2AS08LS02M3B3OMS
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-90763C2651
Generated	2026-08-05

Product Overview

Stainless steel Long-3h Enr 2mm M8 PNP NO+NC Connector M8 4pins

Proximity sensor, inductive, stainless steel, long body, M8, shielded, 2 mm, DC, 4-wire, PNP-Antivalent (NO+NC), M8 4pin plug-in

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Proximity Sensors > E2A
--------------	---------------------------------

Additional Product Information

SizeM8Mounting typeFlushSensing distance2 mmOutput typePNPOperation modeNO + NCConnection methodConnector
M8 - 4 pinMaterial housingStainless steelCable specifications-Overall length of sensor61 mmThread length49 mmDegree of
protection (IP)IP67/IP69K

ETIM for 659342 Sensors (EC002714)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cylinder, screw-thread
Degree of protection (NEMA) (EF011959)
Other
Coating housing (EF001601)
Other
Mechanical mounting condition for sensor (EF004041)
Concise
Performance level according to EN ISO 13849-1 (EF007399)
None
Type of interface for safety communication (EF003956)
None
Type of actuation (EF006949)
Metallic Target
Type of switch function (EF003963)
Anticoincidence
Type of electric connection (EF003961)
Connector M8
Type of interface (EF006977)
None
SIL according to IEC 61508 (EF009889)
None
Housing material (EF001596)
Metal
Type of switching output (EF003962)
PNP
Explosion safety category for gas (EF003997)
None
Cascadable (EF000507)
Yes
With monitoring function downstream switching devices (EF004052)
No
Compression-resistant (EF007106)
No
Suitable for safety functions (EF001597)
No
Number of protected contact energized outputs (EF003952)
0
Number of semiconductor outputs with signalling function (EF003945)
2
Number of protected semiconductor outputs (EF003951)
0
Diameter sensor (EF007111)
8 mm
Switching distance (EF003647)
2 mm
Length of senso...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2A-S08LS02-M3-B3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.