

INDUSTRIAL COMPONENT DATA

E2B-M12LN08-WP-B2 2M E2B 2182B

E2BM12LN08WPB22MOMI OMRON Inductive M12 Long, Non-enr 8mm 3h PNP NC Cable 2m ..

Brand: OMRON | Manufacturer Part Number: E2B-M12LN08-WP-B2 2M



Manufacturer	OMRON
MPN / Reference	E2B-M12LN08-WP-B2 2M
Catalog number	E2BM12LN08WPB22MOMI
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-A1803A6BD7
Generated	2026-08-03

Product Overview

Inductive M12 Long, Non-enr 8mm 3h PNP NC Cable 2m Lite
Proximity sensor, inductive, nickel-brass, long body,M12,unshielded, 8 mm, DC, 3-wire, PNP-NC, 2 m Prewired

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Proximity Sensors > E2B

Additional Product Information

SizeM12Mounting typeNon-flushSensing distance8 mmOutput typePNPOperation modeNCCConnection methodCableMaterial housingBrass, nickel platedCable specificationsPVCCable length2 mOverall length of sensor70 mmThread length46 mmDegree of protection (IP)IP67
ETIM for 674523 Sensors (EC002714)
Feature Name
Feature Value
Explosion safety category for dust (EF003998)
None
Voltage type (EF000187)
DC
Construction type housing (EF004008)
Cylinder, screw-thread

Degree of protection (NEMA) (EF011959)
Other
Coating housing (EF001601)
Nickel-plated
Mechanical mounting condition for sensor (EF004041)
Not flat
Performance level according to EN ISO 13849-1 (EF007399)
None
Type of interface for safety communication (EF003956)
None
Type of actuation (EF006949)
Metallic Target
Type of switch function (EF003963)
Breaker contact
Type of electric connection (EF003961)
Cable
Type of interface (EF006977)
None
SIL according to IEC 61508 (EF009889)
None
Housing material (EF001596)
Metal
Type of switching output (EF003962)
PNP
Explosion safety category for gas (EF003997)
None
Cascadable (EF000507)
Yes
With monitoring function downstream switching devices (EF004052)
No
Compression-resistant (EF007106)
No
Suitable for safety functions (EF001597)
No
Number of protected contact energized outputs (EF003952)
0
Number of semiconductor outputs with signalling function (EF003945)
1
Number of protected semiconductor outputs (EF003951)
0
Diameter sensor (EF007111)
12 mm
Switching distance (EF003647)
8 mm
Length of s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2B-M12LN08-WP-B2 2M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.