

INDUSTRIAL COMPONENT DATA

E2B-M18KS08-M1-B2 E2B 2322A E2BM18KS08M1B2OMI OMRON Inductive M18 Flush 8 mm 3h-PNP NC Connector M12 Lite

Brand: OMRON | Manufacturer Part Number: E2B-M18KS08-M1-B2



Manufacturer	OMRON
MPN / Reference	E2B-M18KS08-M1-B2
Catalog number	E2BM18KS08M1B2OMI
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-C1459B649B
Generated	2026-08-02

Product Overview

Inductive M18 Flush 8 mm 3h-PNP NC Connector M12 Lite

Proximity sensor, inductive, nickel-brass, short body, M18, shielded, 8 mm, DC, 3-wire, PNP NC, M12 connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Proximity Sensors > E2B
--------------	---------------------------------

Additional Product Information

SizeM18Mounting typeQuasi-flushSensing distance8 mmOutput typePNPOperation modeNCConnection methodConnector M12Material housingBrass, nickel platedCable specifications-Overall length of sensor59 mmThread length39 mmDegree of protection (IP)IP67

ETIM for 674473 Sensors (EC002714)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cylinder, screw-thread

Degree of protection (NEMA) (EF011959)
Other
Coating housing (EF001601)
Nickel-plated
Mechanical mounting condition for sensor (EF004041)
Concise
Performance level according to EN ISO 13849-1 (EF007399)
None
Type of interface for safety communication (EF003956)
None
Type of actuation (EF006949)
Metallic Target
Type of switch function (EF003963)
Breaker contact
Type of electric connection (EF003961)
Connector M12
Type of interface (EF006977)
None
SIL according to IEC 61508 (EF009889)
None
Housing material (EF001596)
Metal
Type of switching output (EF003962)
PNP
Explosion safety category for gas (EF003997)
None
Cascadable (EF000507)
Yes
With monitoring function downstream switching devices (EF004052)
No
Compression-resistant (EF007106)
No
Suitable for safety functions (EF001597)
No
Number of protected contact energized outputs (EF003952)
0
Number of semiconductor outputs with signalling function (EF003945)
1
Number of protected semiconductor outputs (EF003951)
0
Diameter sensor (EF007111)
18 mm
Switching distance (EF003647)
8 mm
Length of s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2B-M18KS08-M1-B2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.