

## INDUSTRIAL COMPONENT DATA

# E2B-M30LN30-M1-B1 E2B 2268C E2BM30LN30M1B1OMI OMRON Inductive M30 Long, Non-enr 30mm 3h PNP NA Connector M12..

Brand: OMRON | Manufacturer Part Number: E2B-M30LN30-M1-B1



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | OMRON                      |
| MPN / Reference | E2B-M30LN30-M1-B1          |
| Catalog number  | E2BM30LN30M1B1OMI          |
| Category        | Inductive proximity switch |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-31AEAEA553              |
| Generated       | 2026-08-05                 |

## Product Overview

Inductive M30 Long, Non-enr 30mm 3h PNP NA Connector M12 Lite

Proximity sensor, inductive, nickel-brass, long body, M30, unshielded, 30 mm, DC, 3-wire, PNP NO, M12 connector

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path OMRON &gt; Proximity Sensors &gt; E2B

## Additional Product Information

SizeM30Mounting typeNon-flushSensing distance30 mmOutput typePNPOperation modeNOConnection methodConnector  
M12Material housingBrass, nickel platedCable specifications-Overall length of sensor86 mmThread length51 mmDegree of  
protection (IP)IP67

ETIM for 674536 Sensors (EC002714)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cylinder, screw-thread

Degree of protection (NEMA) (EF011959)  
Other  
Coating housing (EF001601)  
Nickel-plated  
Mechanical mounting condition for sensor (EF004041)  
Not flat  
Performance level according to EN ISO 13849-1 (EF007399)  
None  
Type of interface for safety communication (EF003956)  
None  
Type of actuation (EF006949)  
Metallic Target  
Type of switch function (EF003963)  
Normally open contact  
Type of electric connection (EF003961)  
Connector M12  
Type of interface (EF006977)  
None  
SIL according to IEC 61508 (EF009889)  
None  
Housing material (EF001596)  
Metal  
Type of switching output (EF003962)  
PNP  
Explosion safety category for gas (EF003997)  
None  
Cascadable (EF000507)  
Yes  
With monitoring function downstream switching devices (EF004052)  
No  
Compression-resistant (EF007106)  
No  
Suitable for safety functions (EF001597)  
No  
Number of protected contact energized outputs (EF003952)  
0  
Number of semiconductor outputs with signalling function (EF003945)  
1  
Number of protected semiconductor outputs (EF003951)  
0  
Diameter sensor (EF007111)  
30 mm  
Switching distance (EF003647)  
30 mm  
Leng...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2B-M30LN30-M1-B1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.