

INDUSTRIAL COMPONENT DATA

E2E-X20D230-T 2M E2E 8442F 681874 OMRON Proximity sensor, inductive, brass-nickel, M30, flush, 20 mm, NC, 2 ..

Brand: OMRON | Manufacturer Part Number: E2E-X20D230-T 2M



Manufacturer	OMRON
MPN / Reference	E2E-X20D230-T 2M
Catalog number	E2EX20D230T2MOMS
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-3CA0D4C46C
Generated	2026-08-01

Product Overview

Proximity Sensor, inductive, brass-nickel, M30, shielded, 20 mm, NC, 2 m cable, DC, 2-wire, non-polarity

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Proximity Sensors > New E2E
--------------	-------------------------------------

Additional Product Information

ETIM for 681874 Sensors (EC002714)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cylinder, screw-thread

Degree of protection (NEMA) (EF011959)

Other

Coating housing (EF001601)

Nickel-plated

Mechanical mounting condition for sensor (EF004041)

Quasi-flat

Performance level according to EN ISO 13849-1 (EF007399)

None

Type of interface for safety communication (EF003956)

None

Type of actuation (EF006949)

Metallic Target

Type of switch function (EF003963)

Breaker contact

Type of electric connection (EF003961)

Cable

Type of interface (EF006977)

None

SIL according to IEC 61508 (EF009889)

None

Housing material (EF001596)

Metal

Type of switching output (EF003962)

2-wire

Explosion safety category for gas (EF003997)

None

Cascadable (EF000507)

No

With monitoring function downstream switching devices (EF004052)

No

Compression-resistant (EF007106)

No

Suitable for safety functions (EF001597)

No

Number of protected contact energized outputs (EF003952)

0

Number of semiconductor outputs with signalling function (EF003945)

1

Number of protected semiconductor outputs (EF003951)

0

Diameter sensor (EF007111)

30 mm

Switching distance (EF003647)

20 mm

Length of sensor (EF007334)

60.3 mm

Switching frequency (EF003587)

200 Hz

Number of contact energized outputs with signalling function (EF003946)

0

Supply voltage (EF004127)

10 V

Rated control supply voltage DC (EF003980)

10 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2E-X20D230-T 2M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.