

INDUSTRIAL COMPONENT DATA

E2E-X2D1-M1TGJ-U 0,3M E2E 6090M E2EX2D1M1TGJU03MOMS OMRON 2h cc Enr 2mm M8 NA M12 Connector + 0.3m PUR Cable

Brand: OMRON | Manufacturer Part Number: E2E-X2D1-M1TGJ-U 0,3M



Manufacturer	OMRON
MPN / Reference	E2E-X2D1-M1TGJ-U 0,3M
Catalog number	E2EX2D1M1TGJU03MOMS
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-1C80B7EB96
Generated	2026-08-04

Product Overview

2h cc Enr 2mm M8 NA M12 Connector + 0.3m PUR Cable

Proximity sensor, inductive, M8, shielded, 2 mm, DC, 2-wire, NO, 0.3 m pigtail PUR (increased oil-resistant) with Junction Connector M12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Proximity Sensors > E2E

Additional Product Information

ETIM for 290022 Sensors (EC002714)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cylinder, screw-thread

Degree of protection (NEMA) (EF011959)

Other

Coating housing (EF001601)
Other
Mechanical mounting condition for sensor (EF004041)
Concise
Performance level according to EN ISO 13849-1 (EF007399)
None
Type of interface for safety communication (EF003956)
None
Type of actuation (EF006949)
Metallic Target
Type of switch function (EF003963)
Normally open contact
Type of electric connection (EF003961)
Connector M12
Type of interface (EF006977)
None
SIL according to IEC 61508 (EF009889)
None
Housing material (EF001596)
Metal
Type of switching output (EF003962)
NPN
Explosion safety category for gas (EF003997)
None
Cascadable (EF000507)
No
With monitoring function downstream switching devices (EF004052)
No
Compression-resistant (EF007106)
No
Suitable for safety functions (EF001597)
No
Number of protected contact energized outputs (EF003952)
0
Number of semiconductor outputs with signalling function (EF003945)
1
Number of protected semiconductor outputs (EF003951)
0
Diameter sensor (EF007111)
8 mm
Switching distance (EF003647)
2 mm
Length of sensor (EF007334)
26 mm
Switching frequency (EF003587)
1500 Hz
Number of contact energized outputs with signalling function (EF003946)

0

Rated control supply voltage DC (EF003980)

12 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2E-X2D1-M1TGJ-U 0,3M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.