

INDUSTRIAL COMPONENT DATA

E2E-X4C28-M3 E2EN0070E 698706 OMRON Proximity Sensor, Inductive, SUS Short Body, M8, Shielded, 2mm, DC, 3-Wi..

Brand: OMRON | Manufacturer Part Number: E2E-X4C28-M3



Manufacturer	OMRON
MPN / Reference	E2E-X4C28-M3
Catalog number	E2EX4C28M3OMS
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-84104E0B86
Generated	2026-08-01

Product Overview

Proximity sensor, inductive, short brass body M8, shielded, 4 mm, DC, 3-wire, NPN NC, M8 connector 4 pins

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Proximity Sensors > New E2E

Additional Product Information

Specifications

Size M8

Mounting type Quasi-flush

Sensing distance 4 mm

Overall length of sensor 39 mm

Thread length 21 mm

Material housing Brass, nickel plated

Output type NPN

Operation mode NC

Connection method Connector M8 - 4 pin

Cable specifications -

IO-Link function

IO-Link baud rate Not Applicable

Degree of protection (IP) IP67/IP69K

Accessories

Y92E-J8S12 Mounting Sleeves e-jig for M8 Prox

ETIM for 698706 Sensors (EC002714)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cylinder, screw-thread

Degree of protection (NEMA) (EF011959)

Other

Coating housing (EF001601)

Nickel-plated

Mechanical mounting condition for sensor (EF004041)

Quasi-flat

Performance level according to EN ISO 13849-1 (EF007399)

None

Type of interface for safety communication (EF003956)

None

Type of actuation (EF006949)

Metallic Target

Type of switch function (EF003963)

Breaker contact

Type of electric connection (EF003961)

Connector M8

Type of interface (EF006977)

None

SIL according to IEC 61508 (EF009889)

None

Housing material (EF001596)

Metal

Type of switching output (EF003962)

NPN

Explosion safety category for gas (EF003997)

None

Cascadable (EF000507)

Yes

With monitoring function downstream switching devices (EF004052)

No

Compression-resistant (EF007106)

No

Suitable for safety functions (EF001597)

No

Number of protected contact energized outputs (EF003952)

0

Number of semiconductor outputs with signallin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2E-X4C28-M3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.