

## INDUSTRIAL COMPONENT DATA

# E2E-X50MB1TL30-M1 E2EN2255E 687958 OMRON Proximity sensor, inductive, nickel-brass long body, M30, unshielde..

Brand: OMRON | Manufacturer Part Number: E2E-X50MB1TL30-M1



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | OMRON                      |
| MPN / Reference | E2E-X50MB1TL30-M1          |
| Catalog number  | E2EX50MB1TL30M1OMS         |
| Category        | Inductive proximity switch |
| Minimum order   | 5 Pcs                      |
| Document ID     | EO-5BFC3E8DBD              |
| Generated       | 2026-08-03                 |

## Product Overview

Proximity Sensor, inductive, long body, nickel-brass, M30, without shielding, 50 mm, dc, 3-wire, PNP, NA, IO-Link COM3, connector M12

Proximity sensor, inductive, nickel-brass, long body, M30, unshielded, 50 mm, DC, 3-wire, PNP NO, IO-Link COM3, M12 connector

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                     |
|--------------|-------------------------------------|
| Catalog path | OMRON > Proximity Sensors > New E2E |
|--------------|-------------------------------------|

## Additional Product Information

Specifications

Size M30

Mounting type Non-flush

Sensing distance 50 mm

Overall length 95 mm

Thread length 65 mm

Material housing Brass, nickel plated

Output type IO-Link, PNP

Operation mode NO

Connection method Connector M12

Cable specifications -

IO-Link function

IO-Link baud rate COM3 (230.4 kbps)  
Degree of protection (IP) IP67/IP69K  
ETIM for 687958 Sensors (EC002714)  
Feature Name  
Feature Value  
Degree of protection (NEMA) (EF011959)  
Other  
Mechanical mounting condition for sensor (EF004041)  
Not flat  
Performance level according to EN ISO 13849-1 (EF007399)  
None  
Type of interface for safety communication (EF003956)  
None  
SIL according to IEC 61508 (EF009889)  
None  
Housing material (EF001596)  
Metal  
Explosion safety category for gas (EF003997)  
None  
Explosion safety category for dust (EF003998)  
None  
Voltage type (EF000187)  
DC  
Construction type housing (EF004008)  
Cylinder, screw-thread  
Coating housing (EF001601)  
Nickel-plated  
Type of actuation (EF006949)  
Metallic Target  
Type of switch function (EF003963)  
Normally open contact  
Type of electric connection (EF003961)  
Connector M12  
Type of interface (EF006977)  
Other  
Type of switching output (EF003962)  
PNP  
Cascadable (EF000507)  
Yes  
With monitoring function downstream switching devices (EF004052)  
No  
Compression-resistant (EF007106)  
No  
Suitable for safety functions (EF001597)  
No  
Number of semiconductor outputs with signalling function (EF003945)  
1

Switching frequency (EF003587)

100 Hz

Number of contact energized outputs with signalling fu...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2E-X50MB1TL30-M1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.