

INDUSTRIAL COMPONENT DATA

E2E-X50MB2L30 2M E2EN2244M 698653 OMRON Proximity sensor, inductive, nickel-brass long body, M30, unshielded..

Brand: OMRON | Manufacturer Part Number: E2E-X50MB2L30 2M



Manufacturer	OMRON
MPN / Reference	E2E-X50MB2L30 2M
Catalog number	E2EX50MB2L302MOMS
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-08F59ED584
Generated	2026-08-03

Product Overview

Proximity sensor, inductive, nickel-brass, long body, M30, unshielded, 50 mm, DC, 3-wire, PNP NC, 2 m cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Proximity Sensors > New E2E
--------------	-------------------------------------

Additional Product Information

Specifications

Size M30

Mounting type Non-flush

Sensing distance 50 mm

Overall length of sensor 97.3 mm

Thread length 65 mm

Material housing Brass, nickel plated

Output type PNP

Operation mode NC

Connection method Cable

Cable specifications PVC (oil-resistant)

Cable length 2 m

IO-Link function

IO-Link baud rate Not Applicable

Degree of protection (IP) IP67/IP67G/IP69K

ETIM for 698653 Sensors (EC002714)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cylinder, screw-thread

Degree of protection (NEMA) (EF011959)

Other

Coating housing (EF001601)

Nickel-plated

Mechanical mounting condition for sensor (EF004041)

Not flat

Performance level according to EN ISO 13849-1 (EF007399)

None

Type of interface for safety communication (EF003956)

None

Type of actuation (EF006949)

Metallic Target

Type of switch function (EF003963)

Breaker contact

Type of electric connection (EF003961)

Cable

Type of interface (EF006977)

None

SIL according to IEC 61508 (EF009889)

None

Housing material (EF001596)

Metal

Type of switching output (EF003962)

PNP

Explosion safety category for gas (EF003997)

None

Cascadable (EF000507)

Yes

With monitoring function downstream switching devices (EF004052)

No

Compression-resistant (EF007106)

No

Suitable for safety functions (EF001597)

No

Number of protected contact energized outputs (EF003952)

0

Number of semiconductor outputs with signalling function (EF003945)

1

Number of prote...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2E-X50MB2L30 2M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.