

INDUSTRIAL COMPONENT DATA

E2E2-X5MY2 2M E2E27099H E2E2X5MY22MOMS OMRON

Long 2h NoEnr 5mm M12 NC AC Cable 2m

Brand: OMRON | Manufacturer Part Number: E2E2-X5MY2 2M



Manufacturer	OMRON
MPN / Reference	E2E2-X5MY2 2M
Catalog number	E2E2X5MY22MOMS
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-34A7F76215
Generated	2026-08-03

Product Overview

Long 2h NoEnr 5mm M12 NC AC Cable 2m

Proximity sensor, long body, M12, non shielded, 5 mm, NC, AC, 2-wire, 2 m cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Proximity Sensors > Others

Additional Product Information

ETIM for 233065 Sensors (EC002714)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

AC

Construction type housing (EF004008)

Cylinder, screw-thread

Degree of protection (NEMA) (EF011959)

Other

Coating housing (EF001601)

Nickel-plated

Mechanical mounting condition for sensor (EF004041)

Not flat

Performance level according to EN ISO 13849-1 (EF007399)

None

Type of interface for safety communication (EF003956)

None

Type of actuation (EF006949)

Metallic Target

Type of switch function (EF003963)

Breaker contact

Type of electric connection (EF003961)

Cable

Type of interface (EF006977)

None

SIL according to IEC 61508 (EF009889)

None

Housing material (EF001596)

Metal

Type of switching output (EF003962)

2-wire

Explosion safety category for gas (EF003997)

None

Cascadable (EF000507)

No

With monitoring function downstream switching devices (EF004052)

No

Compression-resistant (EF007106)

No

Suitable for safety functions (EF001597)

No

Number of protected contact energized outputs (EF003952)

0

Number of semiconductor outputs with signalling function (EF003945)

1

Number of protected semiconductor outputs (EF003951)

0

Diameter sensor (EF007111)

12 mm

Switching distance (EF003647)

5 mm

Switching frequency (EF003587)

25 Hz

Number of contact energized outputs with signalling function (EF003946)

0

Rated control supply voltage AC 60 Hz (EF003979)

24 V

Rated control supply voltage AC 50 Hz (EF003978)

24 V

Supply voltage (EF004127)

24 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2E2-X5MY2 2M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.