

## INDUSTRIAL COMPONENT DATA

# E2EQ-X20D230-T 5M E2E 8516C E2EQX20D230T5MOMS

## OMRON Proximity Sensor, inductive, brass-nickel, M30, flush, M..

Brand: OMRON | Manufacturer Part Number: E2EQ-X20D230-T 5M



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | OMRON                      |
| MPN / Reference | E2EQ-X20D230-T 5M          |
| Catalog number  | E2EQX20D230T5MOMS          |
| Category        | Inductive proximity switch |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-3AE68138AD              |
| Generated       | 2026-08-04                 |

### Product Overview

Proximity Sensor, inductive, brass-nickel, M30, flush, M30, shielded, 20 mm, NC, 5 m cable, DC, 2-wire, non-polarity  
Proximity sensor, inductive, brass-nickel, Spatter-coating, M30, shielded, 20 mm, NC, 5 m cable, DC 2-wire, no polarity

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path OMRON &gt; Proximity Sensors &gt; New E2E

### Additional Product Information

ETIM for 681753 Sensors (EC002714)  
Feature Name  
Feature Value  
Explosion safety category for dust (EF003998)  
None  
Voltage type (EF000187)  
DC  
Construction type housing (EF004008)  
Cylinder, screw-thread  
Degree of protection (NEMA) (EF011959)  
Other  
Coating housing (EF001601)

Other

Mechanical mounting condition for sensor (EF004041)

Quasi-flat

Performance level according to EN ISO 13849-1 (EF007399)

None

Type of interface for safety communication (EF003956)

None

Type of actuation (EF006949)

Metallic Target

Type of switch function (EF003963)

Breaker contact

Type of electric connection (EF003961)

Cable

Type of interface (EF006977)

None

SIL according to IEC 61508 (EF009889)

None

Housing material (EF001596)

Metal

Type of switching output (EF003962)

2-wire

Explosion safety category for gas (EF003997)

None

Cascadable (EF000507)

No

With monitoring function downstream switching devices (EF004052)

No

Compression-resistant (EF007106)

No

Suitable for safety functions (EF001597)

No

Number of protected contact energized outputs (EF003952)

0

Number of semiconductor outputs with signalling function (EF003945)

1

Number of protected semiconductor outputs (EF003951)

0

Diameter sensor (EF007111)

30 mm

Switching distance (EF003647)

20 mm

Length of sensor (EF007334)

60.3 mm

Switching frequency (EF003587)

200 Hz

Number of contact energized outputs with signalling function (EF003946)

0

Supply voltage (EF004127)

10 V

Rated control supply voltage DC (EF003980)

10 V

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2EQ-X20D230-T 5M with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.