

INDUSTRIAL COMPONENT DATA

E2EQ-X7B4-M1TJ-IL2 0,3M E2EQ7036G E2EQX7B4M1TJIL203MOMS OMRON Inductive soldering 3h cc Enr 7mm M18 NA/NC M1..

Brand: OMRON | Manufacturer Part Number: E2EQ-X7B4-M1TJ-IL2 0,3M



Manufacturer	OMRON
MPN / Reference	E2EQ-X7B4-M1TJ-IL2 0,3M
Catalog number	E2EQX7B4M1TJIL203MOMS
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-56E6722B19
Generated	2026-08-05

Product Overview

Inductive soldering 3h cc Enr 7mm M18 NA/NC M12 Cable 0.3 m IO LINK COM2

Inductive Welding 3h cc Enr 7mm M18 NA/NC Cable M12 0.3m IO LINK COM2

Proximity sensor, inductive, Fluororesin coating (Base material: brass), short body, M18, shielded, 7mm, DC, 3-wire, PNP NO/NC switching type (Factory

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Proximity Sensors > Others

Additional Product Information

FeaturesIO-Link spatter-resistant proximity sensors as the innovative solution to solve issues at welding application areas of industrial manufacturing sites

IO-Link spatter-resistant proximity sensors as the innovative solution to solve issues at welding application areas of industrial manufacturing sites

Downtime can be reduced through internal diagnostic functions

The sudden failure can be decreased by notifying, if objects being too far or too close

Maintenance operations are more efficient by identification of each sensor through the IO link network

Programmable operation of the sensor reduces the number of models required

The fluororesin coating provides exceptional spatter resistance in welding application areas of automotive or machine tools industries

Ordering information

DC 3-wire IO-Link models

Appearance

Sensing distance

Connection method

Cable specifications

Operation mode

Pin arrangement

Baud rate

Order code

M12

3 mm

Pre-wired models (2 m)

PVC

NO/NC

switching

—

COM2

E2EQ-X3B4-IL2 2M

COM3

E2EQ-X3B4-IL3 2M

M12 Pre-wired Smartclick connector models (0.3 m)

1: +V

3: 0 V

4: C/Q output

COM2

E2EQ-X3B4-M1TJ-IL2 0.3M

COM3

E2EQ-X3B4-M1TJ-IL3 0.3M

M18

7 mm

Pre-wired models (2 m)

—

COM2

E2EQ-X7B4-IL2 2M

COM3

E2EQ-X7B4-IL3 2M

M12 Pre-wired Smartclick connector models (0.3 m)

1: +V

3: 0 V

4: C/Q output

COM2

E2EQ-X7B4-M1TJ-IL2 0.3M

COM3

E2EQ-X7B4-M1TJ-IL3 0.3M

M30

10 mm

Pre-wired models (2 m)

—

COM2

E2EQ-X10B4-IL2 2M

COM3

E2EQ-X10B4-IL3 2M

M12 Pre-wired Smartclick connector m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2EQ-X7B4-M1TJ-IL2 0,3M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.