

INDUSTRIAL COMPONENT DATA

E2EW-X2C112 2M E2EW0081E 695111 OMRON Proximity sensor, inductive, full stainless steel 303 M12, Shielded, 2..

Brand: OMRON | Manufacturer Part Number: E2EW-X2C112 2M



Manufacturer	OMRON
MPN / Reference	E2EW-X2C112 2M
Catalog number	E2EWX2C1122MOMS
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-E460B65DDA
Generated	2026-07-29

Product Overview

Proximity sensor, inductive, full metal stainless steel 303 M12, shielded, 2 mm, DC, 3-wire, NPN NO, 2 m cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Proximity Sensors > Others
--------------	------------------------------------

Additional Product Information

Specifications

Size M12

Mounting type Flush

Sensing distance 2 mm

Output type NPN

Operation mode NO

Connection method Cable

Material housing Stainless steel

Cable specifications PVC

Cable length 2 m

Overall length of sensor 41.9 mm

Thread length 30.4 mm

Features Metal sensing face

Degree of protection (IP) IP67

ETIM for 695111 Sensors (EC002714)

Feature Name
Feature Value
Explosion safety category for dust (EF003998)
None
Voltage type (EF000187)
DC
Construction type housing (EF004008)
Cylinder, screw-thread
Degree of protection (NEMA) (EF011959)
Other
Coating housing (EF001601)
Other
Mechanical mounting condition for sensor (EF004041)
Concise
Performance level according to EN ISO 13849-1 (EF007399)
None
Type of interface for safety communication (EF003956)
None
Type of actuation (EF006949)
Metallic Target
Type of switch function (EF003963)
Normally open contact
Type of electric connection (EF003961)
Cable
Type of interface (EF006977)
None
SIL according to IEC 61508 (EF009889)
None
Housing material (EF001596)
Metal
Type of switching output (EF003962)
NPN
Explosion safety category for gas (EF003997)
None
Cascadable (EF000507)
No
With monitoring function downstream switching devices (EF004052)
No
Compression-resistant (EF007106)
No
Suitable for safety functions (EF001597)
No
Number of protected contact energized outputs (EF003952)
0
Number of semiconductor outputs with signalling function (EF003945)
1
Number of protected semiconductor outputs (EF003951)

0

Diameter sensor (EF007...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E2EW-X2C112 2M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.