

INDUSTRIAL COMPONENT DATA

E32-T11R 5M E32 1568E E32T11R5M OMRON Barrier Flexible Screw M4 cable 5m

Brand: OMRON | Manufacturer Part Number: E32-T11R 5M



Manufacturer	OMRON
MPN / Reference	E32-T11R 5M
Catalog number	E32T11R5M
Category	Optical fibre sensor / optical fibre amplifier
Minimum order	1 Pcs
Document ID	EO-8883C38AE5
Generated	2026-08-03

Product Overview

Barrier Flexible Screw M4 cable 5m
Threaded Flexible Barrier M4 cable 5m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Photoelectric sensors > E32

Additional Product Information

FeaturesStandard cylindrical fiber sensor heads
The standard cylindrical fiber optic sensing heads provide reliable object detection, easy installation and long sensor lifetime for all general applications.
High-flex fibers and 90° cable exit for cable breakage prevention
Models with hexagonal back for simplified one-nut mounting
Sizes M3 to M6
Hi-flex fibers
Hi-flex multicore fibers for flexibility in installation without fiber breakage.
Simple mounting
Models with hexagonal back for simple one-nut mounting.
Fiber breakage prevention
Cable exit shifted by 90° for preventing fiber breakage.
Ordering information
Sensor type

Size

Sensing distance (in mm)1

Order code

Standard fiber

High-flex fiber

Standard fiber

High-flex fiber

E3X-HD

E3NX-FA

E3X-HD

E3NX-FA

M4

1550

2300

1400

1400

E32-TC200 2M

E32-T11R 2M

M3

450

670

130

190

E32-TC200E 2M

E32-T21R 2M

dia 4 mm

1500

2300

-

E32-ETC220 2M

-

M4

-

1000

1500

-

E32-T11N 2M

M6

-

-

1200

1800

-

E32-LR11NP 2M

M6

250

370

-
E32-R21
-
M6
600
900
550
820
E32-DC200 2M
E32-D11R 2M
M4
160
240
60
90
E32-D211 2M
E32-D211R 2M
M3
160
240
150
220
E32-DC200E 2M
E32-D21R 2M
M6
-
350
520
-
E32-D11N 2M
M4
-
350
520
-
E32-D21N 2M
dia 6 mm
220
300
100
150
E32-D14L 2M
E32-D14LR 2M
Specifications
Item
Standard
High Flex

E32-_C200
E32-_C220
E32-D14L
E32-_C200E
E32-D211
E32-R21
E32-_R
E32-T11N
E32-D11N
E32-D14LR
E32-D211R
E32-D21N
E32-LR11NP
Permissible bending radius
R25
R10
R1
R2
Cut to length
Yes
Ambient temperature
-40°C to 70°C
Material
Head
Brass-nickel pla...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E32-T11R 5M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.