

INDUSTRIAL COMPONENT DATA

E3AS-F1500IMT M3 E3AS0013F E3ASF1500IMTM3OMS OMRON Photoelectric sensor, rectangular housing, stainless steel..

Brand: OMRON | Manufacturer Part Number: E3AS-F1500IMT M3



Manufacturer	OMRON
MPN / Reference	E3AS-F1500IMT M3
Catalog number	E3ASF1500IMTM3OMS
Category	Light scanner with background masking
Minimum order	1 Pcs
Document ID	EO-C72737E006
Generated	2026-08-05

Product Overview

Photoelectric sensor, rectangular housing, stainless steel, infrared laser class 1, time-of-flight, 1500 mm, PNP, Light-ON/Dark-ON, IO-Link COM3, M8 4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON
--------------	-------

Additional Product Information

ShapeCuboidSensing methodBackground suppressionSensing distance1500 mmSensing distance (min.)50 mmSetting methodIO-Link, Teach-InConnection methodConnector M8 - 4 pinOutput typeIO-Link, PNPOperation modeDark-ON, Light-ONIO-Link baud rateCOM3 (230.4 kbps)Response time150 msMaterial housingStainless steelProduct Width (unpacked)11.4 mmProduct Height (unpacked)38 mmProduct Depth (unpacked)22 mmType of lightLaser diode, infrared lightLaser class1Spot size95 mmPower supply voltage10-30 VFeaturesTOF (Time of Flight)

ETIM for 690202 Sensors (EC002719)

Feature Name

Feature Value

Degree of protection (NEMA) (EF011959)

Other

Degree of protection (IP) (EF005474)

IP67

Material of optical surface (EF004134)
Plastic
Type of interface for safety communication (EF003956)
Other
Housing material (EF001596)
Metal
Operation agent-safety class (EF003982)
Safety class 3
Explosion safety category for gas (EF003997)
None
Explosion safety category for dust (EF003998)
None
Voltage type (EF000187)
DC
Construction type housing (EF004008)
Cuboid
Laser protection class (EF004027)
Class 1
Setting procedure (EF003994)
Teach-In
Sensing mode (EF007503)
Light-/dark switching
Triangulation (EF008296)
Background fade-out
Type of switch function (EF003963)
Programmable/configurable
Type of electric connection (EF003961)
Connector M8
Type of light (EF004029)
Laser diode, infrared light
Material of cable sheath (EF004136)
Other
Type of switching output (EF003962)
PNP
With communication interface RS-485 (EF007314)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E3AS-F1500IMT M3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.