

INDUSTRIAL COMPONENT DATA

E3AS-HF6000DMT M1H E3AS0207D E3ASHF6000DMTM1HOMS OMRON Photoelectric sensor, aluminum die cast (chrome plati..

Brand: OMRON | Manufacturer Part Number: E3AS-HF6000DMT M1H



Manufacturer	OMRON
MPN / Reference	E3AS-HF6000DMT M1H
Catalog number	E3ASHF6000DMTM1HOMS
Category	Light scanner with background masking
Minimum order	1 Pcs
Document ID	EO-F1C27706F6
Generated	2026-08-03

Product Overview

Photoelectric sensor, aluminum die cast (chrome plating) case, red laser class 1, time-of-flight, diffused beam type, 6000 mm, PNP, Light-ON/Dark-ON, IO-Link COM3, M12 connector (horizontal)

Photoelectric sensor, aluminum die cast (chrome plating) case, red laser class 1, time-of-flight, diffused beam type, 6000 mm, PNP, Light-ON/Dark-ON,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON
--------------	-------

Additional Product Information

ShapeCuboidSensing methodBackground suppressionSensing distance6000 mmSensing distance (min.)50 mmSetting methodIO-Link, Teach-InConnection methodConnector M12Output typeIO-Link, PNPOperation modeDark-ON, Light-ONResponse time2 msMaterial housingAluminiumProduct Width (unpacked)26.5 mmProduct Height (unpacked)58.6 mmProduct Depth (unpacked)68.4 mmType of lightLaser diode, red lightLaser class1Power supply voltage10-30 VFeaturesTOF (Time of Flight)Degree of protection (IP)IP67/IP67G/IP69K

ETIM for 724865 Sensors (EC002719)

Feature Name

Feature Value

Degree of protection (NEMA) (EF011959)

Other

Degree of protection (IP) (EF005474)
IP67
Material of optical surface (EF004134)
Plastic
Type of interface for safety communication (EF003956)
Other
Housing material (EF001596)
Metal
Operation agent-safety class (EF003982)
Safety class 3
Explosion safety category for gas (EF003997)
None
Explosion safety category for dust (EF003998)
None
Voltage type (EF000187)
DC
Construction type housing (EF004008)
Cuboid
Laser protection class (EF004027)
Class 1
Setting procedure (EF003994)
Parameterization
Sensing mode (EF007503)
Light switching
Triangulation (EF008296)
Background fade-out
Type of switch function (EF003963)
Programmable/configurable
Type of electric connection (EF003961)
Connector M12
Type of light (EF004029)
Laser diode, red light
Material of cable sheath (EF004136)
Other
Type of switching output (EF003962)
PNP
With communication interface RS-485 (EF007314)
No
With communication int...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E3AS-HF6000DMT M1H with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.