

INDUSTRIAL COMPONENT DATA

E3FA-LP12-F2 2M E3FA0099G E3FALP12F22MOMS OMRON

Plastic Suppressor funds 200mm PNP light by default Cable 2m

Brand: OMRON | Manufacturer Part Number: E3FA-LP12-F2 2M



Manufacturer	OMRON
MPN / Reference	E3FA-LP12-F2 2M
Catalog number	E3FALP12F22MOMS
Category	Light scanner with background masking
Minimum order	1 Pcs
Document ID	EO-207136F6EF
Generated	2026-08-03

Product Overview

Plastic Suppressor funds 200mm PNP light by default Cable 2m

Photoelectric sensor, M18 threaded barrel, plastic, red LED, background suppression, 200 mm, PNP, Light-ON/Dark-ON, inverted logic, 2 m cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Photoelectric sensors > E3FA / E3RA
--------------	---

Additional Product Information

ShapeCylindrical axialSensing methodBackground suppressionSensing distance200 mmSetting methodFixedConnection methodCableCable length2 mOutput typePNPOperation modeDark-ON, Light-ONResponse time0.5 msMaterial housingABSThread sizeM18Product Length (unpacked)41 mmType of lightPolarity free red lightPower supply voltage10-30 VDegree of protection (IP)IP67/IP69K

ETIM for 659602 Sensors (EC002719)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)
Cylinder, screw-thread
Laser protection class (EF004027)
None
Degree of protection (NEMA) (EF011959)
Other
Degree of protection (IP) (EF005474)
IP67
Setting procedure (EF003994)
Other
Material of optical surface (EF004134)
Plastic
Sensing mode (EF007503)
Light-/dark switching
Type of interface for safety communication (EF003956)
Other
Triangulation (EF008296)
Background fade-out
Type of switch function (EF003963)
Programmable/configurable
Type of electric connection (EF003961)
Cable
Housing material (EF001596)
Plastic
Type of light (EF004029)
Polarity free red light
Material of cable sheath (EF004136)
Polyvinyl chloride (PVC)
Type of switching output (EF003962)
PNP
Operation agent-safety class (EF003982)
Safety class 3
Explosion safety category for gas (EF003997)
None
With communication interface RS-485 (EF007314)
No
Analogue output -10 V ... +10 V (EF006809)
No
With communication interface SSD (EF007315)
No
With communication interface SSI (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E3FA-LP12-F2 2M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.