

INDUSTRIAL COMPONENT DATA

E3FA-RP21-F2 E3FA0104G E3FARP21F2OMS OMRON Plastic Mirror (not included) to 0.1-4m, PNP light by default.M12

Brand: OMRON | Manufacturer Part Number: E3FA-RP21-F2



Manufacturer	OMRON
MPN / Reference	E3FA-RP21-F2
Catalog number	E3FARP21F2OMS
Category	Retroreflective photoelectric sensor
Minimum order	1 Pcs
Document ID	EO-BDD448CBD5
Generated	2026-08-04

Product Overview

Plastic Mirror (not included) to 0.1-4m, PNP light by default.M12

Photoelectric sensor, M18 threaded barrel, plastic, red LED, retro-reflective, 4 m, PNP, Light-ON/Dark-ON, inverted logic, M12 connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Photoelectric sensors > E3FA / E3RA

Additional Product Information

ShapeCylindrical axialSensing methodRetro-reflectiveSensing distance4000 mmSensing distance (min.)100 mmSetting methodManual adjustmentConnection methodConnector M12Output typePNPOperation modeDark-ON, Light-ONResponse time0.5 msMaterial housingABSThread sizeM18Product Length (unpacked)45 mmType of lightPolarized red lightPower supply voltage10-30 VFeaturesM.S.R.Degree of protection (IP)IP67/IP69K

ETIM for 659017 Sensors (EC002717)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cylinder, screw-thread

Laser protection class (EF004027)
None
Degree of protection (NEMA) (EF011959)
Other
Degree of protection (IP) (EF005474)
IP67
Setting procedure (EF003994)
Manual adjustment
Material of optical surface (EF004134)
Plastic
Sensing mode (EF007503)
Light-/dark switching
Type of interface for safety communication (EF003956)
Other
Type of switch function (EF003963)
Programmable/configurable
Type of electric connection (EF003961)
Connector M12
Housing material (EF001596)
Plastic
Type of light (EF004029)
Polarized red light
Type of switching output (EF003962)
PNP
Operation agent-safety class (EF003982)
Safety class 3
Explosion safety category for gas (EF003997)
None
With communication interface RS-485 (EF007314)
No
Analogue output -10 V ... +10 V (EF006809)
No
With communication interface SSD (EF007315)
No
With communication interface SSI (EF007316)
No
Analogue output 0 V ... 10 V (EF006807)
No...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E3FA-RP21-F2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.