

INDUSTRIAL COMPONENT DATA

E3FA-TP11 5M E3FA0077F E3FATP115MOMS OMRON Plastic Barrier 20m PNP Cable 5m

Brand: OMRON | Manufacturer Part Number: E3FA-TP11 5M



Manufacturer	OMRON
MPN / Reference	E3FA-TP11 5M
Catalog number	E3FATP115MOMS
Category	Through beam photoelectric sensor
Minimum order	1 Pcs
Document ID	EO-8E0E218ED2
Generated	2026-07-31

Product Overview

Plastic Barrier 20m PNP Cable 5m

Photoelectric sensor, M18 threaded barrel, plastic, red LED, through-beam, 20 m, PNP, Light-ON/Dark-ON, 5 m cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Photoelectric sensors > E3FA / E3RA

Additional Product Information

ShapeCylindrical axialSensing methodThrough-beamSensing distance20000 mmSetting methodManual
adjustmentConnection methodCableCable length5 mOutput typePNPOperation modeDark-ON, Light-ONResponse time0.5
msMaterial housingABSThread sizeM18Product Length (unpacked)41 mmType of lightPolarity free red lightPower supply
voltage10-30 VDegree of protection (IP)IP67/IP69K
ETIM for 416701 Sensors (EC002716)
Feature Name
Feature Value
Explosion safety category for dust (EF003998)
None
Voltage type (EF000187)
DC
Construction type housing (EF004008)
Cylinder, screw-thread
Scope of delivery of the one-way system (EF004032)

Transmitter and receiver
Laser protection class (EF004027)
None
Degree of protection (NEMA) (EF011959)
Other
Degree of protection (IP) (EF005474)
IP67
Setting procedure (EF003994)
Manual adjustment
Material of optical surface (EF004134)
Plastic
Sensing mode (EF007503)
Light-/dark switching
Type of interface for safety communication (EF003956)
Other
Type of switch function (EF003963)
Programmable/configurable
Type of electric connection (EF003961)
Cable
Housing material (EF001596)
Plastic
Type of light (EF004029)
Polarity free red light
Material of cable sheath (EF004136)
Polyvinyl chloride (PVC)
Type of switching output (EF003962)
PNP
Operation agent-safety class (EF003982)
Safety class 3
Explosion safety category for gas (EF003997)
None
With communication interface RS-485 (EF007314)
No
Analogue output -10 V ... +10 V (EF006809)
No
With communication interface SSD (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E3FA-TP11 5M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.