

INDUSTRIAL COMPONENT DATA

E3NX-MA41 2M E3NX7023R E3NXMA412MOMS OMRON

Amplifier fiber 2 input fiber, digital display, double, fit, smar..

Brand: OMRON | Manufacturer Part Number: E3NX-MA41 2M



Manufacturer	OMRON
MPN / Reference	E3NX-MA41 2M
Catalog number	E3NXMA412MOMS
Category	Optical fibre sensor / optical fibre amplifier
Minimum order	1 Pcs
Document ID	EO-386F69EEDE
Generated	2026-08-01

Product Overview

Amplifier fiber 2 input fiber, digital display, double, fit, smart, multiple functions, 2 PNP outputs, cable 2 m
Fiber amplifier, 2 fiber input, twin digital display, smart tuning, multiple functions, 2 PNP output, 2 m cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Advanced sensors > N-Smart
--------------	------------------------------------

Additional Product Information

ShapeCuboid, rail mountingSensing methodAmplifierSetting methodTeach-InConnection methodCableCable length2 mOutput typePNPOperation modeDark-ON, Light-ONResponse time0.1 msMaterial housingPolycarbonateProduct Width (unpacked)10 mmProduct Height (unpacked)33.5 mmProduct Length (unpacked)71.8 mmType of lightPolarity free red lightPower supply voltage10-30 VFunctionsSelf-diagnosis, Timer, TwinFeatures2 channels, Bank function, Twin outputsApplicationObject detectionDegree of protection (IP)IP50Number of digital outputs2Number of digital inputs0 ETIM for 681532 Sensors (EC002651)

Feature Name

Feature Value

Voltage type (EF000187)

DC

Construction type housing (EF004008)

Cuboid

Laser protection class (EF004027)

Other

Degree of protection (IP) (EF005474)

IP50

Setting procedure (EF003994)

Other

Indication (EF000350)

Digital

Type of switch function (EF003963)

Programmable/configurable

Type of electric connection (EF003961)

Cable

Material fibre optics core (EF004137)

Plastic

Housing material (EF001596)

Plastic

Type of light (EF004029)

Polarized red light

Material of cable sheath (EF004136)

Polyvinyl chloride (PVC)

Type of switching output (EF003962)

PNP

Operation agent-safety class (EF003982)

Safety class 3

Analogue output -10 V ... +10 V (EF006809)

No

Analogue output 0 V ... 10 V (EF006807)

No

Analogue output 0 mA ... 20 mA (EF006808)

No

With blanking function (EF003968)

No

Analogue output 4 mA ... 20 mA (EF006810)

No

With time function (EF003582)

Yes

AWG-number (EF007010)

24

No-load...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / E3NX-MA41 2M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.