

## INDUSTRIAL COMPONENT DATA

# F3SG-4SRA0440-85 F3G28073B 699904 OMRON Safety optical barrier, advanced F3SG-SRA, type 4, 25 mm resolution,..

Brand: OMRON | Manufacturer Part Number: F3SG-4SRA0440-85



|                 |                  |
|-----------------|------------------|
| Manufacturer    | OMRON            |
| MPN / Reference | F3SG-4SRA0440-85 |
| Catalog number  | F3SG4SRA044085   |
| Category        | Light curtain    |
| Minimum order   | 1 Pcs            |
| Document ID     | EO-7917738A45    |
| Generated       | 2026-08-04       |

## Product Overview

Safety Light Curtain, F3SG-SRA Advanced, Type 4, 85 mm resolution, range 0.3 to 20.0 m, height 440 mm, PNP/NPN

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path OMRON > Security Sensors > Barriers F3SG-R

## Additional Product Information

Sensing methodSafety light curtainType of protectionBody protectionNumber of beams6Detection capability85 mmSafety field height440 mmType of safety according to IEC 61496-14Beam spacing80 mmMaximum safety range20 mMinimum operating distance0.3 mKey featuresArea Beam Indicator, Auxiliary output, Blanking, Designated beam output, External Device Monitoring (EDM), External test, Interlock, Muting, Mutual interference prevention, Operating range selection, PNP/NPN selection, Pre-reset, Response time adjustment, Vibration detection, Warning zoneDegree of protection (IP)IP65/IP67/IP67GCascadableNumber of protected semiconductor outputs2Number of semiconductor outputs with signalling function1Type of switching output of the OSSDPNP/NPNResponse time8 msWith muting functionWith beam codingCommunication option(s)Bluetooth, IO-Link, USBSuitable for safety functionsScope of deliveryTransmitter and receiverWavelength of the sensor870 nmConnection methodRoot connector (order separately)Supply voltage DC19.2-28.8 VMax. output current at protected output300 mAAmbient temperature-30-55 °COverall length of sensor440 mmHeight of sensor440 mmWidth of sensor32 mmNumber of fixed side-mount brackets2Number of adjustable side-mount brackets2Number of intermediate brackets0

ETIM for 699904 Sensors (EC002549)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Voltage type (EF000187)

DC

Type of switching output of the OSSD (EF003959)

PNP/NPN

Scope of delivery of the one-way....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / F3SG-4SRA0440-85 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.