

INDUSTRIAL COMPONENT DATA

F3SG-4SRA0680-25-F F3G28041D 699894 OMRON Safety optical barrier, advanced F3SG-SRA, type 4, 25 mm resolution..

Brand: OMRON | Manufacturer Part Number: F3SG-4SRA0680-25-F



Manufacturer	OMRON
MPN / Reference	F3SG-4SRA0680-25-F
Catalog number	F3SG4SRA068025F
Category	Light curtain
Minimum order	1 Pcs
Document ID	EO-CE51BC96EF
Generated	2026-08-06

Product Overview

Safety Light Curtain, F3SG-SRA Advanced, Type 4, 25 mm resolution, range 0.3 to 20.0 m, height 680 mm, PNP/NPN

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Security Sensors > Barriers F3SG-R

Additional Product Information

Specifications

Sensing method Safety light curtain

Type of protection Hand protection

Number of beams 34

Detection capability 25 mm

Safety field height 680 mm

Type of safety according to IEC 61496-1 4

Beam spacing 20 mm

Maximum safety range 20 m

Minimum operating distance 0.3 m

Key features Area Beam Indicator, Auxiliary output, Blanking, Designated beam output, External Device Monitoring (EDM), External test, Interlock, Muting, Mutual interference prevention, Operating range selection, PNP/NPN selection, Pre-reset, Response time adjustment, Vibration detection, Warning zone

Degree of protection (IP) IP65/IP67/IP67G

Cascadable

Number of protected semiconductor outputs 2
Number of semiconductor outputs with signalling function 1
Type of switching output of the OSSD PNP/NPN
Response time 8 ms
With muting function
With beam coding
Communication option(s) Bluetooth, IO-Link, USB
Suitable for safety functions
Scope of delivery Transmitter and receiver
Wavelength of the sensor 870 nm
Connection method Root connector (order separately)
Supply voltage DC 19.2-28.8 V
Voltage type DC
Max. output current at protected output 300 mA
Ambient temperature -30-55 °C
Overall length 680 mm
Height of sensor 38 mm
Width sensor 32 mm
Number of fixed side-mount brackets 2
Number of adjustable side-mount brackets 2
Number of intermediate brackets 0
Accessories
E39-R1S Accessory photosensor, reflector, 40x60x7.5 mm, ABS & Acrylic
E3AS-F1000IPT-M1TJ 0.3M Photoelectric sensor, rectangular housing, pl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / F3SG-4SRA0680-25-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.