

INDUSTRIAL COMPONENT DATA

D4NL-1BFA-B D4NL0004G D4NL1BFAB OMRON Lock makan desert/Opening solen.24vdc 1NC/1NO+2NC LED PG13,5

Brand: OMRON | Manufacturer Part Number: D4NL-1BFA-B



Manufacturer	OMRON
MPN / Reference	D4NL-1BFA-B
Catalog number	D4NL1BFAB
Category	Position switch with guard locking
Minimum order	1 Pcs
Document ID	EO-0EC6201D2C
Generated	2026-08-02

Product Overview

Lock makan desert/Opening solen.24vdc 1NC/1NO+2NC LED PG13,5

Safety door-lock switch, mechanical lock, 24 VDC, 1NC/1NO + 2NC, 10 A, PG 13.5 entry

Guard lock safety-door switch, mechanical lock, 24 VDC, 1NC/1NO + 2NC, 10 A, PG 13.5 entry

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OMRON > Safety > D4DL/DS/DH/DR/GL/NL/NH/NS
--------------	--

Additional Product Information

Door switch typeKey-operatedGuard-lockMaterial housingPlasticMaterial headPlasticAmbient temperature (operating)-10-55 °CConnection methodScrew terminalCable length0 mDirection of operationAdjustableHolding force1300 NDoor contacts NC1Door contacts NO1Lock monitor contacts NC2Lock monitor contacts NO0Lock/Release key typeStandard keyLock/Release key positionBottomLock/Release key materialResinSolenoid voltage24 VLED indicatorDegree of protection (IP)IP67Conduit sizePG13.5Number of conduits2Switch actionSlow actionShapeCuboidOverall length of sensor95 mmHeight of sensor35.5 mmWidth of sensor88.5 mmSwitch without actuatorLock/Release logicPower to unlock (Mechanical lock)

ETIM for 133794 Sensors (EC002593)

Feature Name

Feature Value

Explosion safety category for dust (EF003998)

None

Construction type housing (EF004008)

Special construction
Type of switching contact (EF003591)
Slow-action switch
Degree of protection (NEMA) (EF011959)
Other
Coating housing (EF001601)
Other
Degree of protection (IP) (EF005474)
IP67
Type of interface for safety communication (EF003956)
None
Type of electric connection (EF003961)
Cable entry PG
Type of interface (EF006977)
None
Housing material (EF001596)
Other
Type of guard locking (EF012608)
Quiescent current principle
Explosion safety category for gas (EF003997)
None
With status indication (EF001602)
Yes
Suitable for safety functions (EF001597)
Yes
With escape release (EF007172)
Yes
Number of contacts as change-over contact (EF008257)
0
Number o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / D4NL-1BFA-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.