

INDUSTRIAL COMPONENT DATA

H3CR-A 100-240VAC/100-125VDC H3CR8090D H3CRAAC100240DC100125OMI OMRON Mutifunción 11-pin DPDT

Brand: OMRON | Manufacturer Part Number: H3CR-A 100-240VAC/100-125VDC



Manufacturer	OMRON
MPN / Reference	H3CR-A 100-240VAC/100-125VDC
Catalog number	H3CRAAC100240DC100125OMI
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-837EC76F89
Generated	2026-08-05

Product Overview

Mutifunción 11-pin DPDT

Timer, plug-in, 11-pin, DIN 48 x 48 mm, multifunction, 0.05 s-300 h, DPDT, 5 A, 100 to 240 VAC, 100-125VDC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Timers > H3CR

Additional Product Information

Specifications

Type Analog

Installation type Socket

Functions Multi-functional

Size 1/16 DIN (48 x 48 mm)

Terminal type Plug-in

Operating mode Flicker OFF Start (Signal Start), Flicker ON Start (Signal Start), Interval (Signal Start), OFF Delay (Signal), ON Delay (Signal Start), One-shot Output (Signal Start), Signal ON/OFF Delay

Output type Relay

Contact description DPDT

Time range 0.05 s - 300 h

Supply voltage AC 100-240 V

Supply voltage DC 100-125 V

Number of pin contact 11

Inputs No-voltage

Accessories

P3GA-11 Socket, back-connecting, 11-pin, screw terminals

Y92A-48B Protective cover for DIN 48x48 mm device, hard plastic

Y92F-30 Flush panel mounting adapter for DIN 48x48 mm device

Y92F-73 Adapter for H3CR replacement of STP-YMH timer

ETIM for 667919 Relays (EC001439)

Feature Name

Feature Value

Relay technology category according to IEC 61810-7 (EF016748)

RT I

Degree of protection (IP) (EF005474)

IP40

Voltage type for actuating (EF008242)

AC/DC

Material contact (EF007544)

Other

Material of contact insert (EF008521)

Other

Voltage type (operating voltage) (EF005294)

AC/DC

Material of contact surface (EF004020)

Silver

Type of electric connection (EF003961)

Plug-in connection

Function delay on de-energization (EF003401)

No

Suitable as remote control (EF003362)

No

Suitable for DIN rail (top hat rail) mounting (EF007250)

Yes

Complete with socket (EF003359)

No

Function flashing, starting with pulse, fixed time (EF003364)

No

With semiconductor output (EF003373)

No

Function floati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / H3CR-A 100-240VAC/100-125VDC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.