

INDUSTRIAL COMPONENT DATA

H3CR-A-301 AC24-48/DC12-48 H3CR8103M

H3CRA301AC2448DC1248OMI OMRON Multifunction 48x48

Brand: OMRON | Manufacturer Part Number: H3CR-A-301 AC24-48/DC12-48



Manufacturer	OMRON
MPN / Reference	H3CR-A-301 AC24-48/DC12-48
Catalog number	H3CRA301AC2448DC1248OMI
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-96749056C9
Generated	2026-07-29

Product Overview

Multifunction 48x48

Timer, plug-in, 11-pin, 1/16DIN (48 x 48 mm), multifunction, 0.1s-600h, DPDT, 5 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Timers > H3CR

Additional Product Information

Specifications

Type Analog

Installation type Socket

Functions Multi-functional

Size 1/16 DIN (48 x 48 mm)

Terminal type Plug-in

Operating mode Flicker OFF Start (Signal Start), Flicker ON Start (Signal Start), Interval (Signal Start), OFF Delay (Signal), ON Delay (Signal Start), Signal ON/OFF Delay

Output type Relay

Contact description DPDT

Time range 0.1 s - 600 h

Supply voltage AC 24-48 V

Supply voltage DC 12-48 V

Number of pin contact 11

Inputs No-voltage

Accessories

P3GA-11 Socket, back-connecting, 11-pin, screw terminals

Y92A-48B Protective cover for DIN 48x48 mm device, hard plastic

Y92F-30 Flush panel mounting adapter for DIN 48x48 mm device

Y92F-73 Adapter for H3CR replacement of STP-YMH timer

ETIM for 667930 Relays (EC001439)

Feature Name

Feature Value

Relay technology category according to IEC 61810-7 (EF016748)

RT I

Material of contact insert (EF008521)

Other

Degree of protection (IP) (EF005474)

IP40

Voltage type (operating voltage) (EF005294)

AC/DC

Material of contact surface (EF004020)

Silver

Voltage type for actuating (EF008242)

AC/DC

Type of electric connection (EF003961)

Plug-in connection

Material contact (EF007544)

Other

Function delay on de-energization (EF003401)

No

Suitable as remote control (EF003362)

No

Outputs, reversible delayed/undelayed (EF006988)

No

Function pulse shaping (EF003403)

No

Suitable for DIN rail (top hat rail) mounting (EF007250)

Yes

Complete with socket (EF003359)

No

Function star-delta (EF003380)

No

Function floating contact on energ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / H3CR-A-301 AC24-48/DC12-48 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.