

INDUSTRIAL COMPONENT DATA

H5CX-AD-N H5CX6006D H5CXADNOMI OMRON SPDT Standard 12-24Vdc/24Vac Screw

Brand: OMRON | Manufacturer Part Number: H5CX-AD-N



Manufacturer	OMRON
MPN / Reference	H5CX-AD-N
Catalog number	H5CXADNOMI
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-B00BDF7C35
Generated	2026-08-04

Product Overview

SPDT Standard 12-24Vdc/24Vac Screw

Timer, DIN 48x48 mm, IP66, 4 preset & 4 actual time digits, multi range 0.01 s to 9999 h (10 ranges), multifunction, NPN/PNP/No voltage input selectab

Timer, DIN 48x48 mm, IP66, 4 preset & 4 actual time digits, multi range 0.01 s to 9999 h (10 ranges), multifunction, NPN/PNP/No voltage input selectable, SPDT 5 A relay output, 12-24 VDC/24 VAC supply, includes color change display function

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Timers > H5CX

Additional Product Information

Specifications

Type Digital

Installation type On-panel

Functions Multi-functional

Size 1/16 DIN (48 x 48 mm)

Terminal type Screw

Output type Relay

Contact description SPDT

Time range 0.001 s - 9999 h

Supply voltage AC 24-24 V

Supply voltage DC 12-24 V

Inputs Gate (NPN/PNP), Reset (NPN/PNP), Signal (NPN/PNP)

Accessories

Y92A-48 Protective cover for DIN48x48mm device, hard plastic (shallow)

Y92A-48F1 Protective cover for DIN 48 x 48 mm timer and counter, soft plastic

Y92F-45 Panel adaptor, 48 x 48 device into 67 x 67 hole

ETIM for 668625 Relays (EC001439)

Feature Name

Feature Value

Relay technology category according to IEC 61810-7 (EF016748)

RT I

Degree of protection (IP) (EF005474)

IP66

Voltage type for actuating (EF008242)

AC/DC

Material contact (EF007544)

Other not-copper alloys

Material of contact insert (EF008521)

Other

Voltage type (operating voltage) (EF005294)

AC/DC

Material of contact surface (EF004020)

Untreated

Type of electric connection (EF003961)

Screw connection

Function delay on de-energization (EF003401)

Yes

Suitable as remote control (EF003362)

No

Suitable for DIN rail (top hat rail) mounting (EF007250)

No

Complete with socket (EF003359)

Yes

Function flashing, starting with pulse, fixed time (EF003364)

Yes

With semiconductor output (EF003373)

No

Function floating contact on de-energization (EF003402)

Yes

Outputs, reversible delayed/undelayed (EF006988)

No

Function pulse shaping (EF003403)

Yes

Function star-delta (EF003380)

No

Function floating contact on ene...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / H5CX-AD-N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.