

INDUSTRIAL COMPONENT DATA

H5CX-L8-N H5CX6008M H5CXL8NOMI OMRON SPDT Basic 100-240Vac Octal

Brand: OMRON | Manufacturer Part Number: H5CX-L8-N



Manufacturer	OMRON
MPN / Reference	H5CX-L8-N
Catalog number	H5CXL8NOMI
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-B2AEB25CF2
Generated	2026-08-01

Product Overview

SPDT Basic 100-240Vac Octal

Timer, plug-in, 8-pin, DIN 48x48 mm, IP66, 4 preset & 4 actual time digits, multi range 0.01 s to 9999 h (10 ranges), economy model, NPN/PNP/No voltag

Timer, plug-in, 8-pin, DIN 48x48 mm, IP66, 4 preset & 4 actual time digits, multi range 0.01 s to 9999 h (10 ranges), economy model, NPN/PNP/No voltage input selectable, SPDT 5 A relay output, 100-240 VAC supply

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Timers > H5CX

Additional Product Information

Specifications

Type Digital

Installation type DIN rail, On-panel, Socket

Functions Multi-functional

Size 1/16 DIN (48 x 48 mm)

Terminal type Plug-in

Output type Relay

Contact description SPDT

Time range 0.001 s - 9999 h

Supply voltage AC 100-240 V

Number of pin contact 8

Inputs Reset (NPN), Signal (NPN)

Accessories

P3G-08 Socket, back-connecting, 8-pin, screw terminals

Y92A-48 Protective cover for DIN48x48mm device, hard plastic (shallow)

Y92A-48F1 Protective cover for DIN 48 x 48 mm timer and counter, soft plastic

Y92F-30 Flush panel mounting adapter for DIN 48x48 mm device

Y92F-45 Panel adaptor, 48 x 48 device into 67 x 67 hole

Y92S-29 Waterproof packing for use with 48x48mm devices and Y92F30 flush mounting adapter

ETIM for 668607 Relays (EC001439)

Feature Name

Feature Value

Relay technology category according to IEC 61810-7 (EF016748)

RT I

Material of contact insert (EF008521)

Other

Degree of protection (IP) (EF005474)

IP66

Voltage type (operating voltage) (EF005294)

AC/DC

Material of contact surface (EF004020)

Untreated

Voltage type for actuating (EF008242)

AC/DC

Type of electric connection (EF003961)

Screw connection

Material contact (EF007544)

Other not-copper alloys

Function delay on de-energization (EF003401)

Yes

Suitable as remote control (EF003362)

No

Outputs, reversible delayed/undelayed (EF006988)

No

Function pulse shaping (EF003403)

Yes

Suitable for DIN rail (top hat rail) mounting (EF007250)

Yes

Complete with socket (EF003359)

Yes

Function star-delta (EF003380...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / H5CX-L8-N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.