

INDUSTRIAL COMPONENT DATA

H5CX-L8S-N H5CX6009R H5CXL8SNOMI OMRON Output Transistor Basic 12-24Vdc/Vac Octal

Brand: OMRON | Manufacturer Part Number: H5CX-L8S-N



Manufacturer	OMRON
MPN / Reference	H5CX-L8S-N
Catalog number	H5CXL8SNOMI
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-96FC947078
Generated	2026-08-03

Product Overview

Output Transistor Basic 12-24Vdc/Vac Octal

Basic Transistor Output 12-24Vdc/Vac Octal

Timer, plug-in, 8-pin, DIN48x48mm, IP66, 4 preset & 4 actual time digits, multi range 0.01s to 9999h (10 ranges), economy model, NPN/PNP/No voltage in

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OMRON > Timers > H5CX

Additional Product Information

FeaturesThe most complete digital standard timer on the market

H5CX offers you the most complete series of products on the market today. Based on extensive customer research, these new timers have been designed with added-value features that users both need and appreciate.

H 48 x W 48 x D 59 to 78mm

Three-colour display value, red, green or orange

Models with Instantaneous Contact Outputs

0.001 s to 9999 h, 10 ranges

Input NPN, PNP and contact

Sealed timers

The front of the H5CX is NEMA4X (IP66 equivalent) so it is sealed against the ingress dust and water. This means that they can be used in many applications that other timers can not. Easily adjustable through the front keys or for more security the keys can be disabled to prevent malicious or accidental tampering. Simple settings can be made either via dip switches or a

simple to follow menu structure to suite the installer.

Harsh environment

Control products can be subjected to harsh environments where they can be splashed during the process or covered in dust or get warm through their location. The E5CN, E5CSV, H7CX, H5CX and K3HB all feature a NEMA4X (IP66 equivalent) front panels so are suitable for the use in these applications, also the low profile fascia means that they are less prominent in the front of the panel and so less likely to become dirty.

Ordering information

Output type

Supply voltage

Functions

External connection

Size in mm (H×W×D)

Inputs

Order code

Contact output

100 to 240 VAC

A:Signal ON-delay

A-1:S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OMRON / H5CX-L8S-N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.